

stern



TOTAL TOUCHLESS EXPERIENCE



“ Since 1989, Stern Engineering has been at the forefront of designing and manufacturing cutting-edge, sustainable touch-free fixtures for commercial washrooms. ”



DESIGN INNOVATION

Since 1989, Stern Engineering has been at the forefront of designing and manufacturing cutting-edge, sustainable touch-free fixtures for commercial washrooms. Being a leader in Green Building and LEED practices, using Stern's touchless faucets, soap dispensers, hand dryers, "Behind-The-Mirror" - mirrored wash stations, urinals, dual flush valves, and shower panels can help any project maximize sustainability and water conservation.

Expanding on this expertise, Stern has introduced its latest innovation: patented Touchless Cubicles. This new product complements the Total Touchless Washroom concept, offering seamless functionality and hygiene in every aspect of the design.

As both a manufacturer and a one-stop shop for architects, interior designers and fit-outs, Stern provides fully customizable options to meet specific project needs, ensuring flexibility and tailored solutions for any commercial space.

Understanding the importance of functional beauty, Stern maintains design consistency across the entire project, while prioritizing the user experience to create a comfortable, elegant, and sustainable environment that delivers the same sense of privacy and comfort in public washrooms as one would find at home.



ALWAYS COMMITTED TO GREEN BUILDING
AND WATER-EFFICIENT PRODUCTS

STERN “LEEDS” THE WAY

Stern: Your Partner in Water Conservation and LEED Certification

Stern Engineering supports sustainable construction with cutting-edge, touchless fixtures designed for exceptional water efficiency, helping projects achieve the highest LEED certification levels.

Under LEED v5, Stern products excel in the Water Efficiency (WE) category, earning up to **6 points** through significant water savings:

- **Toilet Flush Valves:** Reduce usage to **1.1 gpf**, saving 14% more water.
- **Urinal Flush Valves:** Ultra-low-flow models at **0.125 gpf** achieve a 75% reduction.
- **Touchless Faucets:** Flow rates as low as **0.15 gpm**, delivering up to 70% water savings.
- **Shower Heads:** Save 47% water, using just **1.06 gpm**.

Stern’s solutions not only meet but exceed LEED v5 standards, maximizing water conservation while ensuring exceptional hygiene and functionality. Partner with Stern for sustainable, environmentally responsible building practices.

Commercial Fixtures, Fittings, and Appliances	LEED v5 Baseline (IP Units)	LEED v5 Baseline (SI Units)	Stern Best Solutions (IP Units)	Stern Best Solutions (SI Units)	Water Savings (%)
Flush Valves for Toilets	1.28 gallons per flush (gpf)	4.8 liters per flush (lpf)	Single Flush: 1.1 gpf	Single Flush: 4.2 lpf	14%
Flush Valves for Urinals	0.5 gpf	1.9 lpf	Ultra-Low Flow: 0.125 gpf	Ultra-Low Flow: 0.5 lpf	75%
Touchless Faucets	0.5 gallons per minute (gpm) at 60 psi	1.9 liters per minute (lpm) at 415 kPa	0.35 gpm / 0.15 gpm (adjustable)	1.32 lpm / 0.57 lpm (adjustable)	30% / 70%
Shower Heads	2.0 gpm at 80 psi	7.6 lpm at 550 kPa	1.06 gpm at 50 psi	4.0 lpm at 350 kPa	47%
Water Reuse Systems	No baseline requirement	No baseline requirement	Rainwater/Greywater Reuse Available	Rainwater/Greywater Reuse Available	N/A

* Touchless Faucets: reflect the ability to operate at 0.15 gpm for up to 70% water savings, alongside the standard 0.35 gpm setting for 30% water savings.

* Water Reuse Systems: Savings depend on implementation and local water supply usage; therefore, a percentage cannot be calculated.



Notes:

- 1. LEED v5 Standards:**
 - o Updated baselines focus on water efficiency and incentivize ultra-low flow fixtures and reuse systems.
 - o Projects can earn additional credits by surpassing these baselines.
- 2. Stern Best Solutions:**
 - o Stern’s fixtures outperform LEED v5 baselines, helping achieve maximum water efficiency credits.
 - o Stern products allow for flexible water-saving solutions tailored to meet project needs while maximizing LEED points.
 - o The dual faucet flow options provide builders with enhanced opportunities to achieve water efficiency go
 - o Products like touchless faucets and ultra-low flow urinals promote sustainability and hygiene.

WHAT'S NEW?

Cubicles

- Touchless Cubicles
- Floor-to-Ceiling Cubicles
- Restricted Access Cubicles
- ADA Accessible Automatic Cubicle

FOR MORE INFORMATION, REQUEST THE STERN CUBICLE CATALOGUE.

TOI - Top Occupancy Indicator

Smart LED occupancy indicators seamlessly integrated into the handle and lock and also at the top of the cubicle, offering an intuitive and efficient experience for users. A great high-traffic washroom solution, Top Occupancy Indicators (TOI) ensure clear visibility of availability from a distance, promoting hygiene, social distancing, and smart design.

Restricted Access Cubicles

The Restricted Access Cubicles with an electronic keypad, provides an effective way to manage access control. These access control systems require the users to enter a unique code to unlock and open the door. Great for a matching storage area and/or location for employees to change uniforms.

VacantView Washroom Display

Stern's VacantView Washroom Display, a Best of BDNY Product Winner, enhances hygiene and reduces crowding by instantly showing cubicle availability, minimizing wait times and congestion. Perfect for high-traffic environments like airports and malls, it ensures better traffic flow, improved visitor experience, and a cleaner, safer washroom.

Stern's SWAR Bridge Cabinets

Stern's SWAR Bridge, Top and Side Cabinets offer a versatile storage solution with optional configurations to maximize space and enhance design. Seamlessly integrating with SWAR units, these cabinets combine customizable options and sleek craftsmanship for a cohesive, sophisticated interior.

Boreal Faucet and Soap Dispenser Matching Set

The Boreal Faucet and Soap Dispenser are designed as a perfectly matching pair, bringing water and soap together in seamless harmony. With sleek contours, straight lines, and a unified square design, they deliver a cohesive, chic look for any modern washroom.

Stern Trio

Matching Soap, Water, and Air
The Stern Trio offers a perfectly matching set of soap dispenser, faucet, and hand dryer for a cohesive, streamlined design. Available in deck or wall-mounted options, and also stainless steel AISI316, this all-in-one solution combines style and function, delivering a clean, modern aesthetic for any washroom.

360°
Sustainable hygiene
Total Touchless Experience

Cubicles



Touchless Cubicles

Stern's Patented Touchless Cubicles offer unmatched versatility, allowing effortless switching between touchless sensor-activated entry and exit, as well as optional manual operation. Designed for user-friendly convenience and flexibility, they redefine modern washroom solutions with innovative design.



For more details and inquiries go to
www.touclesscubicles.com




Restricted Access Cubicles

The Restricted Access Cubicles with an electronic keypad, provides an effective way to manage access control. These access control systems require the users to enter a unique code to unlock and open the door. Great for a matching storage area and/or location for employees to change uniforms.



Stern's Floor-To-Ceiling Manual Cubicles

Stern's Floor-to-Ceiling Manual Cubicles combine durability and style, offering long-lasting performance without compromising aesthetics. Featuring a customizable selection of HPL colors, Matte Black or Stainless hardware, occupancy indicators, and self-closing hinges, they are built to withstand heavy use while maintaining a sleek, pristine appearance.



TOI - Top Occupancy Indicator

Stern's Touchless Cubicles feature smart LED occupancy indicators integrated into the handle and lock, providing an intuitive and efficient user experience. For high-traffic washrooms, Top Occupancy Indicators (TOI) offer clear visibility of availability from afar, enhancing hygiene, social distancing, and modern design.



Stern's VacantView Washroom Display

Stern's VacantView Washroom Display improves hygiene and reduces crowding by instantly showing cubicle availability. Ideal for high-traffic spaces, it improves traffic flow while delivering a better customer experience and a cleaner, safer washroom environment.



ADA Accessible Automatic Cubicle

Stern's Patented ADA Accessible Automatic Cubicle combines intelligent, touch-free door technology to deliver a hygienic, inclusive, and design-forward solution for modern public restrooms. Engineered for maximum privacy and comfort, it's ideal for high-traffic environments seeking a total touchless experience.

GREAT DESIGN STARTS WITH THE PERFECT FINISH

Advancements in technology and a growing focus on purposeful design have transformed customization and style in the commercial washroom. By introducing finishes to projects, design continuity is brought into the public restroom, enhancing both aesthetics and creating a more comfortable experience for visitors.



POLISHED CHROME

Polished Chrome offers a refined, durable finish that resists rust and corrosion while remaining cost-effective and easy to clean. Created through electroplating, this graceful finish is Stern's default, combining elegance with long-lasting performance.



MATTE BLACK

Matte Black finishes are achieved through powder coating, an electrostatic process that creates a flexible, durable layer resistant to corrosion, flaking, and scratching. Exceptionally versatile and easy to clean, this finish minimizes the visibility of dirt, water spots, and fingerprints, offering both style and practicality.



PVD COATING (PHYSICAL VAPOR DEPOSITION)

PVD Coating (Physical Vapor Deposition) involves vaporizing a solid material in a vacuum and depositing it onto the fixture's surface. This process creates a thin, bonded metal layer that enhances both appearance and durability, offering select products in a range of premium finishes.

*Selected products are available in a variety of special finishes:



PVD BRUSHED NICKEL

Popular for its "stainless steel" appearance, PVD Brushed Nickel creates a sophisticated and cool look that hides fingerprints and water spots.



PVD COPPER

With its warm, velvety finish, PVD Copper adds a touch of elegance and depth to contemporary and industrial designs. This unique finish stands out for its rich tone and luxurious appeal, making it a perfect choice for creating bold, sophisticated spaces.



PVD ANTIQUE BRONZE

Rich and dramatic, PVD Antique Bronze brings a striking touch of sophistication to any design. With its deep, textured finish, it adds warmth and character, complementing both classic and modern spaces. This unique finish not only enhances the ambiance with its timeless appeal but also offers durability.


STAINLESS STEEL AISI316

Stainless Steel AISI316 is a high-performance material that combines elegant design with exceptional durability. With no need for additional finishing, the material itself provides corrosion resistance, strength, and easy maintenance. Built to withstand even the harshest conditions, this series offers a sleek, vandal-resistant solution for long-lasting performance.



 EXTREME CS AISI316	 D28 AISI316	 TUBULAR AISI316	 SMART AISI316
 TRENDY AISI316	 ELITE AISI316	 CSABA AISI316	 GREEN AISI316
 EXTREME AISI316	 EXTREME CS SOAP DESPENSER AISI316	 TUBULAR SOAP DESPENSER AISI316	 SMART SD AISI316
 TRENDY FOAM AISI316	 Elite SD AISI316	 CSABA SD AISI316	 GREEN 28 SD AISI316
 TUBULAR HAND DRYER AISI316	 EVER HD AISI316	 NOBLE 2032	 JUPITER 2040





SWAR, BEHIND THE MIRROR
PRODUCTS, & HAND DRYERS

1-16



DECK MOUNTED FAUCETS

17-42



WALL-MOUNTED FAUCETS

43-56



SOAP DISPENSERS &
HAND SANITIZERS

57-90



IRON FRAME SETS

91-98



URINALS & TOILETS

99-116



SHOWER PANELS &
SHOWER CONTROLS

117-130




PROGRAMMING SOLUTIONS
& COMPONENTS

131-141



SWAR, BEHIND THE MIRROR, & HAND DRYERS

	SWAR SOAP WATER AIR REVOLUTION LINE	3-10		BEHIND THE MIRROR PAPER HOLDER	13
	SWA HI-SPEED MODULE	11		BEHIND THE MIRROR SOAP DISPENSER	14
	RECESSED MOUNTING DUO	12		EVER HAND DRYER	15
	BEHIND THE MIRROR FAUCET	13		TUBULAR HAND DRYER	15

SWAR TV




Complete Mirrored Wash Station With 23.5" TV


Includes high speed hand dryer, touch free faucet, touch free soap dispenser, mixing valve, and LED pictograms, whose color and sequence can be customized by remote control, help for intuitive user guidance and decoration.

Moreover, the award-winning mirror monitor can be incorporated into the cabinet, allowing for the display of user information, advertisements, or entertainment. With Stern's advanced, all-in-one hand-washing station, you can bring take your next bathroom project to the forefront of modernity.

- 280461 **SWAR TV**, 12V transformer



SWAR WITH MULTIFEED



Customizable SWAR with Multifeed has an Integrated 6-Liter Soap Tank with Option for 2 or 3 Connected Cabinet System.

The great look of the Deluxe Customizable SWAR, but made for hi-traffic projects with an option for 3 or 2 interconnected cabinets.

It comes with the multifeed kit, a 6 Liter soap reservoir that internally connects to the coordinating soap dispensers – a quick and easy centralized refill point for cleaning staff.

Also includes high-speed hand dryer, mixing valve, touch-free faucet, touch-free soap dispenser, and LED pictograms for intuitive user guidance and decoration.

Delivered with remote controls to adjust soap dosage, select light color or sequence, and customize the faucet settings, this innovative wash station offers an unparalleled user experience.



Customization Options:

Size: Tailored dimensions to fit your specific space requirements.

Color: Available in a wide range of finishes to match your design aesthetic.

Components: Select from a variety of touchless fixtures and features.

LED Colors for Icons: LED icon colors and color sequence adjustable by remote control.

Bridge Cabinets: Additional storage and design flexibility for enhanced functionality.

Key Benefits:

- Eliminates messy, slippery floors, and long lines for hand washing.
- Reduces the amount of labor for commercial facilities maintenance.
- Electrical connection supplied according to your region/needs.



SWAR

Complete Sanitary Cabinet with a Lockable Mirror

Includes high speed hand dryer, touch free faucet, touch free soap dispenser, mixing valve, and LED pictograms, whose color and sequence can be customized by remote control, help for intuitive user guidance and decoration.

Delivered with remote controls to adjust soap dosage, select light color or sequence and customize the faucet settings.

- Eliminates messy, slippery floors, and long lines for hand washing.
- Reduces the amount of labor for commercial facilities maintenance.
- Electrical connection supplied according to your region / needs.

Customization Options:


Size: Tailored dimensions to fit your specific space requirements.

Color: Available in a wide range of finishes to match your design aesthetic.

Components: Select from a variety of touchless fixtures and features.

LED Colors for Icons: Adjustable by remote for personalized visual cues.

Bridge Cabinets: Additional storage and design flexibility for enhanced functionality.



- 280460-US **SWAR US**, 12V transformer
- 280460-UK **SWAR UK**, 12V transformer
- 280460-EU **SWAR EU**, 12V transformer
- 280460-HW **SWAR HARDWIRED**, 12V transformer



- 280460 **SWAR**, 12V transformer



- 280470 **SWAR P**, 12V transformer
Includes: hand dryer, mixing valve, touch-free faucet, soap dispenser, and paper towel dispenser



- 280476 **SA MODULE**, 12V transformer
Includes: touch-free soap dispenser and hand dryer

BRIDGE CABINETS FOR SWAR

Decorative Fixed Bridge Cabinet

Stern's bridge cabinets are specialized mirror cabinets designed to seamlessly fill the gap between two adjacent SWAR cabinets or between a wall and a SWAR cabinet. These innovative additions ensure a continuous, cohesive look while maximizing functionality and storage space.


Key Features:

Flexible Sizes: Customizable dimensions to perfectly fit your project requirements.

Color Options: Available in a range of finishes to complement the SWAR cabinets and overall design aesthetic.

Seamless Integration: Designed to enhance the visual appeal while maintaining consistency in style and functionality.

This decorative fixed bridge cabinet is the perfect solution to create a polished and unified washroom environment.



PAPER MODULE

A decorative fixed cabinet that is used as a concealed paper option and made to coordinate with Stern's Duo or Trio. The mirrored paper module can be used as a stand-alone to create a beautiful cohesive design.

Product Details:

- With or without internal shelves
- With or without lock
- Top opening or side opening (left or right) according to your needs.



SWAR CITY

Mirrored Wash Station for Compact Spaces and Budget

Includes high-speed hand dryer, touch-free faucet, touch-free soap dispenser, and LED pictograms for intuitive user guidance and decoration in one color.


Delivered with remote control to adjust soap dosage and customize the faucet settings, this compact and budget-friendly solution is perfect for smaller spaces without compromising on functionality or aesthetics.

MDF color options in either white or black.

Cabinet sizes available in 600 mm or 800 mm.

- Eliminates messy, slippery floors, and long lines for hand washing.
- Reduces the amount of labor for commercial facilities maintenance.
- Electrical connection supplied according to your region/needs.

- 280455 **SWAR CITY**



CHOOSE YOUR SWAR

	Stern's SWAR TV	Stern's Original SWAR	Stern's SWAR City
Product Features	All-in-one customizable sanitary cabinet with integrated TV monitor allowing the display of travel info, ads, or entertainment. Choose the size, color, components, and accessories for your projects needs.	Customizable all-in-one sanitary cabinet - choose the size, color, components, and accessories for your projects needs.	Standard model with basic options of the all-in-one sanitary cabinet.
Water Temperature	Integrated mixer to adjust the temperature.	Install with either a thermostatic mixing valve or mixer.	Optional thermostatic mixing valve.
Length	800 mm Other tailored sizes available upon request.	550 mm – 800 mm width 900 mm – 1000 mm height	600 mm or 800 mm
Material	MDF with customizable colors to match any design concept.	MDF with customizable colors to match any design concept.	Available in White or Black
Mirror & indicative icons	4 mm thick glass mirror with full MDF inside. Illuminated LED pictograms for intuitive user's guide and decoration. The color of the light or a sequence of colors can be customized using the provided remote control.	4 mm thick glass mirror with full MDF inside. Illuminated LED pictograms for intuitive user's guide and decoration. LED illuminated icons color and sequence can be customized using the remote control.	4 mm thick glass mirror with full MDF inside. White LED illuminated icons.
Soap tank capacity.	6-liter tank automatic soap dispenser. Soap can be primed with the provided remote control or with the individual button at the pump.	6-liter tank automatic soap dispenser. Soap can be primed with the provided remote control or with the individual button at the pump.	6-liter tank automatic soap dispenser. Soap can be primed with the provided remote control or with the individual button at the pump.
Soap viscosity	Since Stern's pump is peristaltic, it works with a wide range of viscosities for both: - Foam - up to 100 cPs - Liquid - from 100 to up to 3,800 cPs	Since Stern's pump is peristaltic, it works with a wide range of viscosities for both: - Foam - up to 100 cPs - Liquid - from 100 to up to 3,800 cPs	Soap pump is peristaltic and works with liquid soap from 100 cPs to up to 3,800 cPs.
Optional features & accessories	Refill indicator to be displayed at the soap icon. Halo Lighting.	Refill indicator to be displayed at the soap icon. Halo Lighting.	Thermostatic mixing valve



DEPARTURES				
TIME	DEPARTMENTS	FLIGHTS	WAVE	REMARKS
08:15	0800	FLIGHT	FLIGHT	
08:30	0800	FLIGHT	FLIGHT	
08:45	0800	FLIGHT	FLIGHT	
09:00	0800	FLIGHT	FLIGHT	
09:15	0800	FLIGHT	FLIGHT	
09:30	0800	FLIGHT	FLIGHT	
09:45	0800	FLIGHT	FLIGHT	
10:00	0800	FLIGHT	FLIGHT	
10:15	0800	FLIGHT	FLIGHT	
10:30	0800	FLIGHT	FLIGHT	
10:45	0800	FLIGHT	FLIGHT	
11:00	0800	FLIGHT	FLIGHT	
11:15	0800	FLIGHT	FLIGHT	
11:30	0800	FLIGHT	FLIGHT	
11:45	0800	FLIGHT	FLIGHT	
12:00	0800	FLIGHT	FLIGHT	
12:15	0800	FLIGHT	FLIGHT	
12:30	0800	FLIGHT	FLIGHT	
12:45	0800	FLIGHT	FLIGHT	
13:00	0800	FLIGHT	FLIGHT	
13:15	0800	FLIGHT	FLIGHT	
13:30	0800	FLIGHT	FLIGHT	
13:45	0800	FLIGHT	FLIGHT	
14:00	0800	FLIGHT	FLIGHT	
14:15	0800	FLIGHT	FLIGHT	
14:30	0800	FLIGHT	FLIGHT	
14:45	0800	FLIGHT	FLIGHT	
15:00	0800	FLIGHT	FLIGHT	
15:15	0800	FLIGHT	FLIGHT	
15:30	0800	FLIGHT	FLIGHT	
15:45	0800	FLIGHT	FLIGHT	
16:00	0800	FLIGHT	FLIGHT	
16:15	0800	FLIGHT	FLIGHT	
16:30	0800	FLIGHT	FLIGHT	
16:45	0800	FLIGHT	FLIGHT	
17:00	0800	FLIGHT	FLIGHT	
17:15	0800	FLIGHT	FLIGHT	
17:30	0800	FLIGHT	FLIGHT	
17:45	0800	FLIGHT	FLIGHT	
18:00	0800	FLIGHT	FLIGHT	
18:15	0800	FLIGHT	FLIGHT	
18:30	0800	FLIGHT	FLIGHT	
18:45	0800	FLIGHT	FLIGHT	
19:00	0800	FLIGHT	FLIGHT	
19:15	0800	FLIGHT	FLIGHT	
19:30	0800	FLIGHT	FLIGHT	
19:45	0800	FLIGHT	FLIGHT	
20:00	0800	FLIGHT	FLIGHT	
20:15	0800	FLIGHT	FLIGHT	
20:30	0800	FLIGHT	FLIGHT	
20:45	0800	FLIGHT	FLIGHT	
21:00	0800	FLIGHT	FLIGHT	
21:15	0800	FLIGHT	FLIGHT	
21:30	0800	FLIGHT	FLIGHT	
21:45	0800	FLIGHT	FLIGHT	
22:00	0800	FLIGHT	FLIGHT	
22:15	0800	FLIGHT	FLIGHT	
22:30	0800	FLIGHT	FLIGHT	
22:45	0800	FLIGHT	FLIGHT	
23:00	0800	FLIGHT	FLIGHT	
23:15	0800	FLIGHT	FLIGHT	
23:30	0800	FLIGHT	FLIGHT	
23:45	0800	FLIGHT	FLIGHT	
00:00	0800	FLIGHT	FLIGHT	
00:15	0800	FLIGHT	FLIGHT	
00:30	0800	FLIGHT	FLIGHT	
00:45	0800	FLIGHT	FLIGHT	
01:00	0800	FLIGHT	FLIGHT	
01:15	0800	FLIGHT	FLIGHT	
01:30	0800	FLIGHT	FLIGHT	
01:45	0800	FLIGHT	FLIGHT	
02:00	0800	FLIGHT	FLIGHT	
02:15	0800	FLIGHT	FLIGHT	
02:30	0800	FLIGHT	FLIGHT	
02:45	0800	FLIGHT	FLIGHT	
03:00	0800	FLIGHT	FLIGHT	
03:15	0800	FLIGHT	FLIGHT	
03:30	0800	FLIGHT	FLIGHT	
03:45	0800	FLIGHT	FLIGHT	
04:00	0800	FLIGHT	FLIGHT	
04:15	0800	FLIGHT	FLIGHT	
04:30	0800	FLIGHT	FLIGHT	
04:45	0800	FLIGHT	FLIGHT	
05:00	0800	FLIGHT	FLIGHT	
05:15	0800	FLIGHT	FLIGHT	
05:30	0800	FLIGHT	FLIGHT	
05:45	0800	FLIGHT	FLIGHT	
06:00	0800	FLIGHT	FLIGHT	
06:15	0800	FLIGHT	FLIGHT	
06:30	0800	FLIGHT	FLIGHT	
06:45	0800	FLIGHT	FLIGHT	
07:00	0800	FLIGHT	FLIGHT	
07:15	0800	FLIGHT	FLIGHT	
07:30	0800	FLIGHT	FLIGHT	
07:45	0800	FLIGHT	FLIGHT	
08:00	0800	FLIGHT	FLIGHT	



LED PICTOGRAMS

PAPER DISPENSER

MIXER

6L TANK

HAND DRYER

SOAP DISPENSER

FAUCET

CUSTOMIZABLE OPTIONS:

SOAP

- Soap Dispenser
- Foam Dispenser
- 6-liter Tank
- 2-liter Tank
- No Soap Dispenser

RINSE

- Cold Water
- Premixed Water
- Cartridge Mixer
- Thermostatic Mixer

DRY

- Touch-Free Hand Dryer
- Paper Dispenser

Once you've made your selections for the interior products, you can then choose your cabinet dimensions:

- Width
- Length
- Depth (for Paper Dispenser)
- Color

NEW CUSTOMIZATION OPTIONS:



REFILL INDICATOR
The refill icon will show when the soap needs to be refilled.



THERMOSTATIC MIXING VALVE
As a new customization possibility, you can now configure SWAR with Stern's TMV (ASSE 1070, NSF 371, TMV3, and DVGW certified) instead of the default cartridge mixer.



AMBIENT HALO LIGHTING
Create ambiance with the glow of Halo Lighting for SWAR TV or SWAR.



CURVED EDGE MIRROR
Give a smooth look to SWAR by choosing a mirror with rounded corners.

SWA HI-SPEED MODULE


Complete system including high-speed hand dryer, thermostatic mixing valve, touch-free faucet, liquid soap dispenser and optional soap level indicator projection.

- Ready to be integrated behind the mirror for a clear, minimalistic design.
- Eliminates messy, slippery floors, and long lines for hand washing.
- Reduces the amount of labor for commercial facilities maintenance.
- Easy installation with a stainless steel frame to be fixed to the wall.
- Ideal touch-free soap-water-air cycle.
- Helps prevent cross contamination.
- Reduces water and soap consumption.
- To be used with non-proprietary soap.
- Drying time: less than 15 seconds.


- 280410 12V transformer




Complete system including high-speed hand dryer (1), thermostatic mixing valve (2), touch-free faucet (3) liquid soap dispenser (4)




Modular system including high-speed hand dryer (1), touch-free faucet (2) and liquid soap dispenser (3)



Modular system including touch-free faucet (3) and liquid soap dispenser (4)



Modular system including high-speed hand dryer (1) and liquid soap dispenser (4)



Modular system including thermostatic mixing valve (2), touch-free faucet (3) and liquid soap dispenser (4)



*numbers of products included are based on the image above.

RECESSED MOUNTING DUO


Touchless soap dispenser and faucet for recessed mounting behind the mirror or panel

Complete system including TMV to limit the hot water temperature and Soap and Water remote control.

- 280500 RECESSED MOUNTING DUO



with Extreme CS duo



with Tubular duo



TAILORED TO YOUR NEEDS:

The SWA Module's complete version includes a touch-free soap or foam dispenser, faucet, thermostatic mixing valve and hand dryer. Each component can be delivered individually with any combination you prefer.



* System including paper dispenser instead of hand dryer also available upon request




STAINLESS
STEEL
AISI316
OPTION

BTM FAUCET


Electronic wall-mounted faucet for integration behind the mirror

- Drastically reduces water consumption
- No physical contact. Helps to protect users against cross contamination
- Sensor settings adjustable by remote control
- Easy installation behind the mirror
- Matching IR operated soap dispenser
- 280310 **BTM B**, Battery box for 6 x 1.5V AA batteries
- 280300 **BTM E**, 9V transformer




BTM PAPER TOWEL HOLDERS

- Stainless steel
- For integration behind-the-mirror as part of the SWA electronic wall mounted system
- Easy installation
- The High-Capacity paper towel holder saves space and is a functional solution that accommodates standard paper towels from your favorite brands (paper towels not included)
- 03300148 **PAPER TOWEL HOLDER - SWAR**



- Stainless steel
- For integration behind-the-mirror as part of the SWA electronic wall mounted system
- Easy installation
- The standard sized paper towel holder saves space and is a functional solution that accommodates standard paper towels from your favorite brands (paper towels not included)
- 03300148 **PAPER TOWEL HOLDER - CITY**




BTM SOAP/FOAM DISPENSER

Touch-free electronic soap dispenser for integration behind the mirror

- Drastically reduces soap consumption
- No physical contact. Helps to protect users against cross contamination
- Peristaltic pump. The soap is driven inside the soap tube without contact with the pump, preventing contamination and back flow
- Accurate soap dosage
- To be used with non-proprietary liquid and foam soap for maximum savings
- Easy to install and refill
- Matching IR operated faucet



1L




BEHIND MIRROR SD

Delivers liquid soap/foam

- 280210 **BEHIND MIRROR SD B**, Battery box for six (6) D batteries
- 280200 **BEHIND MIRROR SD E**, 12V Transformer
- 280250 **BTM FOAM E**, 12V Transformer

6L




MF BEHIND MIRROR SD/FOAM

MF BTM SD CS

MF BEHIND MIRROR SD

Soap dispenser to be used with Stern's Multifeed kits for multiple refill. Delivers liquid soap/ foam.

- 07292223 **MF BEHIND MIRROR SD**, 12V Transformer
- 07292270 **MF BEHIND MIRROR FOAM**, 12V Transformer
- 07292278 **MF BTM SD CS**, 12V Transformer



BTM SD CS


Concealed spout
Delivers liquid soap/foam

- 280225 **BTM SD CS B**, Battery box for six (6) D batteries
- 280220 **BTM SD CS E**, 12V Transformer

MULTIFEED KIT


Allows multiple soap dispenser refill (up to 6 dispensers) with a single 1.6 US Gallons (6 liters) tank.

- 07220096 **MULTIFEED KIT**



EVER HD

Electronic deck-mounted hand dryer Operated by IR sensor
Touch-free electronic hand dryer for deck-mounted installations.
Powered by 110V-120/220V-240VAC.
Hand dryer will automatically shut off after being used for more than 60 seconds. Sensor settings can be customized by remote control.
Includes motor and heater thermal protection in case of overheating.




- EVER HD**
- 230510 **EVER HD**, 110V-120/220V-240VAC
 - 230520 **EVER HD AISI316**, 110V-120/220V-240VAC



TUBULAR HD

Electronic wall-mounted hand dryer Operated by IR sensor
Touch-free electronic hand dryer for wall-mounted installations.
Powered by 110V-120/220V-240VAC.
Hand dryer will automatically shut off after being used for more than 60 seconds. Sensor settings can be customized by remote control.
Includes motor and heater thermal protection in case of overheating.



- TUBULAR HD**
Concealed installation in dry walls
110V-120/220V-240VAC
- 350030 **TUBULAR HD**
 - 350040 **TUBULAR HD AISI316**
- TUBULAR DP HD**
Concealed installation in dry walls as well as concrete and brick walls
110V-120/220V-240VAC
- 350020 **TUBULAR DP HD**
 - 350010 **TUBULAR DP HD AISI316**

- Advantages:**
- HEPA filter for added hygienic properties
 - Full brass body or stainless steel 316 material
 - Variety of colors and special finishes available
 - Matching touch-free faucet and soap dispenser
 - Long lasting, durable and vandal resistant
 - Air flow intensity adjustable by external button
 - Adjustability with remote control: security time, detection range, delay out
 - On/Off function to perform cleaning





LAVATORY FAUCETS



BOREAL

20



GREEN

35



CSABA

21



CLASSIC

36



CSABA 2-IN-1

22



EASY

37



TRENDY

23 - 26



SWAN

38



EXTREME

27 - 29



CONDOR

39



QUADRAT DM

30



DOLPHIN

41



ELITE

31 - 32



COOL TF

42



SMART

33 - 34




NEW!

BOREAL SERIES

Electronic lavatory faucet operated by IR sensor


The stylish and modern Boreal faucet includes options for cold or premixed water, as well as hot and cold water. The IR sensor is built into the body for more resistance to vandalism.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




BOREAL

- 212000 **BOREAL B**, 6 X 1.5V AA batteries
- 212005 **BOREAL E**, 9V Transformer




BOREAL 1000

- 212050 **BOREAL 1000 B**, 6 X 1.5V AA batteries
- 212055 **BOREAL 1000 E**, 9V Transformer



BOREAL PLUS

- 212010 **BOREAL PLUS B**, 6 X 1.5V AA batteries
- 212015 **BOREAL PLUS E**, 9V Transformer




BOREAL 1000 PLUS

- 212060 **BOREAL 1000 PLUS B**, 6 X 1.5V AA batteries
- 212065 **BOREAL 1000 PLUS E**, 9V Transformer


CSABA SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water. Activated by concealed IR sensor built into the spout.
IP67 dual power input box that allows the faucet to be used with 9V battery and can be powered by a 9V transformer which includes an integrated back up system to be used with a 9V lithium battery enabling the faucet to be used normally in case of power failure.
Comes in option for Stainless steel AISI 316.
Customized finishes also available to match all design concepts.


WATER SAVING OPTIONS		
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray
4 LPM	1.0 GPM	PCA Spray




- CSABA**
- 233000 **CSABA B**, 9V Battery
 - 233010 **CSABA E**, 9V Transformer
- CSABA AISI316**
- Stainless steel AISI 316 body
- 233003 **CSABA B AISI316**, 9V Battery
 - 233016 **CSABA E AISI316**, 9V Transformer



- CSABA 1000**
- Mixer to adjust water temperature
- 233020 **CSABA 1000 B**, 9V Battery
 - 233030 **CSABA 1000 E**, 9V Transformer
- CSABA 1000 AISI316**
- Stainless steel AISI 316 body
- 233033 **CSABA 1000 E AISI316**, 9V Transformer



- CSABA PLUS**
- Tall version
- 233050 **CSABA PLUS B**, 9V Battery
 - 233051 **CSABA PLUS E**, 9V Transformer
- CSABA PLUS AISI316**
- Stainless steel AISI 316 body
- 233053 **CSABA PLUS AISI316 B**, 9V Battery
 - 233054 **CSABA PLUS E AISI316**, 9V Transformer




- CSABA PETITE**
- Petite version
- 233042 **CSABA PETITE B**, 9V Battery
 - 233040 **CSABA PETITE E**, 9V Transformer
- CSABA PETITE AISI316**
- Stainless steel AISI 316 body
- 233045 **CSABA PETITE B AISI316**, 9V Battery

CSABA 2-IN-1 SERIES

Electronic lavatory faucet and soap dispenser operated by IR sensor
Touch-free deck-mounted electronic faucet and soap dispenser in a single unit that are activated by concealed sensors built into the spouts.
Ultimate retrofit option as it only requires a single hole in the deck for a touch free faucet and soap dispenser.

WATER SAVING OPTIONS		
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray
4 LPM	1.0 GPM	PCA Spray



- CSABA 2-IN-1**
- 233013 **CSABA 2-IN-1**, 12V Transformer



TRENDY SERIES


Electronic lavatory faucet operated by IR sensor

Series includes options for cold or premixed water as well as hot and cold water, long spout, tall versions for counter top sinks and ring illumination models.

Furthermore, this series includes a solenoid valve, located inside the product, which makes it more resistant to vandalism.


Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




TRENDY PLUS
Tall version for counter top wash basins

- 239050 **TRENDY PLUS B**, 9V Battery
- 239150 **TRENDY PLUS E**, 9V Transformer



TRENDY 1000 PLUS
Tall version for counter top wash basins
Mixer to adjust water temperature

- 239250 **TRENDY 1000 PLUS B**, 9V Battery
- 239350 **TRENDY 1000 PLUS E**, 9V Transformer




TRENDY

- 239000 **TRENDY B**, 9V Battery
- 239100 **TRENDY E**, 9V Transformer

TRENDY AISI316
Stainless steel AISI 316 body

- 239003 **TRENDY B AISI316**, 9V Battery
- 239103 **TRENDY E AISI316**, 9V Transformer




TRENDY L
Long spout 90mm

- 239400 **TRENDY LB**, 9V Battery
- 239500 **TRENDY LE**, 9V Transformer


TRENDY L AISI316
Stainless steel AISI 316 body

- 239403 **TRENDY LB AISI316**, 9V Battery
- 239404 **TRENDY LE AISI316**, 9V Transformer



TRENDY 1000
Mixer to adjust water temperature

- 239200 **TRENDY 1000 B**, 9V Battery
- 239300 **TRENDY 1000 E**, 9V Transformer



TRENDY 1000 L
Mixer to adjust water temperature
Long spout 90mm

- 239600 **TRENDY 1000 LB**, 9V Battery
- 239700 **TRENDY 1000 LE**, 9V Transformer



TRENDY T SERIES

Electronic lavatory faucet operated by IR sensor

Features an integrated thermostatic mixer for an anti-scalding operation and temperature control.

Trendy T ensures the water is temperature-balanced and helps prevent users from burning their hands.

Additional Advantages:

- Lead free
- Thermostatic control for optimal temperature
- Including an internal comfort stopper that allows you to set the maximum temperature according to your preference
- Ideal for the healthcare sector
- Internal solenoid valve

TEMPERATURE FEATURES


HOT LIMIT STOPPER - Mechanical mechanism for built in maximum temperature control at 48.9°C (120°F), factory set. Other values available upon request

COMFORT STOP - Option to limit the hot water temperature from 38°C (100.4°F) to 48.9°C (120°F).

FIXED TEMPERATURE - Allows the technical staff to set a consistent temperature and fix the faucet cap to a specific temperature.




WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray



TRENDY T

Integrated thermostatic mixer to adjust water temperature


- 236930 **TRENDY TB**, 9V Battery
- 236935 **TRENDY TE**, 9V Transformer




EXTREME SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water, long spout and tall versions for counter top sinks.
Furthermore, this series includes a solenoid valve, located inside the product, which makes it more resistant to vandalism.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray





- EXTREME**
- 237200 **EXTREME B**, 9V Battery
 - 237300 **EXTREME E**, 9V Transformer




- EXTREME 1000**
Mixer to adjust water temperature
- 237100 **EXTREME 1000 B**, 9V Battery
 - 237000 **EXTREME 1000 E**, 9V Transformer

- EXTREME HL**
Long spout 176mm.
Body diameter Ø38. Dual power input box. When powered by a 9V transformer features an integrated backup system to be used with a 9V Lithium Battery, which enables the product to be used normally in case of a power failure.
- 237317 **EXTREME HLB**, 9V Battery
 - 237316 **EXTREME HLE**, 9V Transformer
 - 237340 **EXTREME HLB LF**, 9V Battery, Lead Free version
 - 237341 **EXTREME HLE LF**, 9V Transformer, Lead Free version



- EXTREME PLUS**
Tall version for counter top wash basins
- 237250 **EXTREME PLUS B**, 9V Battery
 - 237350 **EXTREME PLUS E**, 9V Transformer



- EXTREME 1000 PLUS**
Tall version for counter top wash basins
Mixer to adjust water temperature
- 237150 **EXTREME 1000 PLUS B**, 9V Battery
 - 237050 **EXTREME 1000 PLUS E**, 9V Transformer




EXTREME LF SERIES

Electronic lavatory faucet operated by IR sensor

Lead free faucet for cold or premixed water as well as hot and cold water, with a concealed sensor integrated into the spout.

Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.


WATER SAVING OPTIONS		
4 LPM	1 GPM	Honeycomb TT
1.89 LPM	0.5 GPM	PCA Spray



EXTREME LF

Lead free version with concealed sensor at the spout


- 237820 **EXTREME LFB**, 9V Battery
- 237810 **EXTREME LFE**, 9V Transformer



EXTREME 1000 LF

Mixer to adjust water temperature


- 237102 **EXTREME 1000 LFB**, 9V Battery
- 237003 **EXTREME 1000 LFE**, 9V Transformer



EXTREME LF AISI316

Stainless steel AISI 316 body. Ideal for medical and coastal environments

- 237821 **EXTREME LFB AISI316**, 9V Battery
- 237811 **EXTREME LFE AISI316**, 9V Transformer



EXTREME 1000 LF AISI316

Stainless steel AISI 316 body
Mixer to adjust water temperature


- 237103 **EXTREME 1000 LFB AISI316**, 9V Battery
- 237004 **EXTREME 1000 LFE AISI316**, 9V Transformer

QUADRAT DM SERIES

Electronic lavatory faucet operated by IR sensor


Series includes options for cold or premixed water as well as hot and cold water.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray



QUADRAT DM

- 351020 **QUADRAT DM B**, 6 X 1.5V AA batteries
- 351010 **QUADRAT DM E**, 9V Transformer



QUADRAT 1000 DM


- 351500 **QUADRAT 1000 DM B**, 6 X 1.5V AA batteries
- 351510 **QUADRAT 1000 DM E**, 9V Transformer



ELITE SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water, long spout and tall versions for counter top sinks.
Furthermore, this series includes a solenoid valve, located inside the product, which makes it more resistant to vandalism.
Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




ELITE PLUS
Tall version for counter top wash basins

- 236350 **ELITE PLUS B**, 9V Battery
- 236450 **ELITE PLUS E**, 9V Transformer

ELITE AISI316
Stainless steel AISI 316 body

- 236453 **ELITE PLUS E AISI316**, 9V Transformer




ELITE

- 236300 **ELITE B**, 9V Battery
- 236400 **ELITE E**, 9V Transformer

ELITE AISI316
Stainless steel AISI 316 body

- 236303 **ELITE B AISI316**, 9V Battery
- 236404 **ELITE E AISI316**, 9V Transformer




ELITE 1000
Mixer to adjust water temperature

- 236700 **ELITE 1000 B**, 9V Battery
- 236800 **ELITE 1000 E**, 9V Transformer


ELITE 1000 AISI316
Stainless steel AISI 316 body.

- 236803 **ELITE 1000 E AISI316**, 9V Transformer




ELITE 1000 PLUS
Tall version for counter top wash basins
Mixer to adjust water temperature

- 236750 **ELITE 1000 PLUS B**, 9V Battery
- 236850 **ELITE 1000 PLUS E**, 9V Transformer




ELITE L
Extra long spout 138mm

- 236500 **ELITE LB**, 9V Battery
- 236600 **ELITE LE**, 9V Transformer



ELITE 1000 L
Mixer to adjust water temperature
Extra long spout 138mm

- 236550 **ELITE 1000 LB**, 9V Battery
- 236650 **ELITE 1000 LE**, 9V Transformer



ELITE 1000 with Technician's Mixer
Mixer to adjust water temperature
Option to remove the mixing handle to allow maintenance staff only, to adjust water temperature


- 236720 **ELITE 1000 B with Technician's Mixer**, 9V Battery
- 236805 **ELITE 1000 E with Technician's Mixer**, 9V Transformer




SMART SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water, long spout and tall versions for counter top sinks.
Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.


WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




- SMART**
- 235100 **SMART B**, 9V Battery
 - 235200 **SMART E**, 9V Transformer
- SMART AISI316**
- 235104 **SMART B AISI316**, 9V Battery
 - 235204 **SMART E AISI316**, 9V Transformer




- SMART 1000**
Mixer to adjust water temperature
- 235500 **SMART 1000 B**, 9V Battery
 - 235600 **SMART 1000 E**, 9V Transformer



- SMART L**
Extra long spout 90mm
- 235110 **SMART LB**, 9V Battery
 - 235210 **SMART LE**, 9V Transformer
- SMART L AISI316**
- 235113 **SMART LB AISI316**, 9V Battery
 - 235213 **SMART LE AISI316**, 9V Transformer




- SMART 1000 L**
Extra long spout 90mm
Mixer to adjust water temperature
- 235510 **SMART 1000 LB**, 9V Battery
 - 235610 **SMART 1000 LE**, 9V Transformer



- SMART PLUS**
Tall version for counter top wash basins
- 235150 **SMART PLUS B**, 9V Battery
 - 235250 **SMART PLUS E**, 9V Transformer

- SMART PLUS AISI316**
- 235151 **SMART PLUS B AISI316**, 9V Battery
 - 235251 **SMART PLUS E AISI316**, 9V Transformer




- SMART 1000 PLUS**
Tall version for counter top wash basins
Mixer to adjust water temperature
- 235550 **SMART 1000 PLUS B**, 9V Battery
 - 235650 **SMART 1000 PLUS E**, 9V Transformer


GREEN SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water. Includes ring illuminated versions (electronically operated).
Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.


WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




- GREEN AB1953**
- 225901 **GREEN AB1953**, Internal 9V Battery
- GREEN AISI316**
- 225901-316 **GREEN AISI316**, Internal 9V Battery



- GREEN 1000 AB1953**
Mixer to adjust water temperature
- 225801 **GREEN 1000 AB1953**, Internal 9V Battery



- GREEN B/E AB1953**
- 225951 **GREEN B AB1953**, 9V Battery
 - 225941 **GREEN E AB1953**, 9V Transformer
- GREEN AISI316**
- 225901-316 **GREEN AISI316**, Internal 9V Battery




- GREEN 1000 B/E AB1953**
Mixer to adjust water temperature
- 225871 **GREEN 1000 B AB1953**, 9V Battery
 - 225821 **GREEN 1000 E AB1953**, 9V Transformer
- GREEN 1000 AISI316**
Mixer to adjust water temperature
- 225873 **GREEN 1000 B AISI316**, 9V Battery
 - 225824 **GREEN 1000 E AISI316**, 9V Transformer

CLASSIC SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA STREAM
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA SPRAY
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA SPRAY




- CLASSIC CS**
Concealed sensor
- 293100 **CLASSIC CS B**, 9V Battery
 - 293200 **CLASSIC CS E**, 9V Transformer



- CLASSIC AB1953**
- 291010 **CLASSIC AB1953**, Internal 9V Battery

- CLASSIC B/E AB1953**
- 291110 **CLASSIC B AB1953**, 9V Battery
 - 291210 **CLASSIC E AB1953**, 9V Transformer




- CLASSIC 1000 AB1953**
Mixer to adjust water temperature
- 292020 **CLASSIC 1000 B AB1953**, Internal 9V Battery

- CLASSIC 1000 B/E AB1953**
Mixer to adjust water temperature
- 292120 **CLASSIC 1000 B AB1953**, 9V Battery
 - 292230 **CLASSIC 1000 E AB1953**, 9V Transformer


EASY SERIES

Electronic lavatory faucet operated by IR sensor
This structure is a one piece solid brass for added vandal resistance.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA STREAM
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA SPRAY
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA SPRAY



- EASY**
Cold or premixed water
- 246010 **EASY B**, 9V Battery
 - 246020 **EASY E**, 9V Transformer



- EASY 1000**
Option to remove the mixing handle to allow maintenance staff only, to adjust water temperature
- 246050 **EASY 1000 B**, 9V Battery
 - 246060 **EASY 1000 E**, 9V Transformer




EASY WITH COVERPLATE
see page 138


SWAN SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water.
Furthermore, this series includes a solenoid valve, located inside the product, which makes it more resistant to vandalism.


WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA STREAM
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA SPRAY
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA SPRAY




- SWAN 1010 AB1953**
- 250220 **SWAN 1010 AB1953**, Internal 9V Battery



- SWAN 1000 AB1953**
Mixer to adjust water temperature
- 252210 **SWAN 1000 AB1953** Internal 9V Battery



- SWAN 1010 B/E AB1953**
- 250310 **SWAN 1010 B AB1953**, 9V Battery
 - 250420 **SWAN 1010 E AB1953**, 9V Transformer



- SWAN 1000 B/E AB1953**
Mixer to adjust water temperature
- 252310 **SWAN 1000 B AB1953**, 9V Battery
 - 252420 **SWAN 1000 E AB1953**, 9V Transformer


CONDOR SERIES

Electronic lavatory faucet operated by IR sensor

For cold or premixed water.


IP67 Dual power input box that allows the faucet to be used with a 9V battery. Can be also be powered by a 9V transformer which includes an integrated backup system to be used with a 9V Lithium battery. This enables the product to be used normally in case of a power failure.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA STREAM
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA SPRAY
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA SPRAY



CONDOR 1010

- 210100 **CONDOR 1010**, 9V Battery
- 210300 **CONDOR 1010 E**, 9V Transformer



CONDOR

Integrated panel versions


- 210000 **CONDOR**, 9V Battery
- 210200 **CONDOR E**, 9V Transformer




DOLPHIN SERIES

Electronic lavatory faucet operated by IR sensor
Series includes options for cold or premixed water as well as hot and cold water.


WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA STREAM
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA SPRAY
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA SPRAY



- DOLPHIN FB**
- 270170 **DOLPHIN FB**, 9V Battery
 - 270180 **DOLPHIN FE**, 9V Transformer




- DOLPHIN 1000 FB**
Mixer to adjust water temperature
Internal solenoid
- 270320 **DOLPHIN 1000 FB**, 9V Battery
 - 270330 **CDOLPHIN 1000 FE**, 9V Transformer




- DOLPHIN GB**
Gooseneck tall spout
- 270120 **DOLPHIN GB**, 9V Battery
 - 270220 **DOLPHIN GE**, 9V Transformer

COOL TF SERIES

Touch-free electronic glass or bottle filler faucet activated by IR sensor



- COOL TF**
Long reach spout
- 280150 **COOL TFB**, 9V Battery
 - 280140 **COOL TFE**, 9V Transformer



- COOL TF G**
- 280160 **COOL TF GB**, 9V Battery
 - 280170 **COOL TF GE**, 9V Transformer



WALL MOUNTED FAUCETS

	EXTREME CS	45		NARA Q	52
---	------------	----	---	--------	----

	MALMO	46		MEDICAL	53 - 54
---	-------	----	---	---------	---------

	TUBULAR	47 - 48		WASHFREE 1000	55
---	---------	---------	---	---------------	----

	D28	49-50		PROX, WAVE & TOUCH SOLUTIONS	56
--	-----	-------	--	---------------------------------	----

	CUBICA	51
---	--------	----

TUBULAR SERIES

Electronic wall mounted faucet Operated by IR sensor


Series includes options for cold or premixed water as well as hot and cold water, long spout and various installation options.

Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




STAINLESS
STEEL
AISI316
OPTION



TUBULAR

Concealed installation in dry walls


- 350200 **TUBULAR B**, 6 x 1.5 AA Batteries
- 350100 **TUBULAR E**, 9V Transformer



TUBULAR 2030

Concealed installation in concrete or brick walls


- 350300 **TUBULAR 2030 B**, 9V Battery
- 350400 **TUBULAR 2030 E**, 9V Transformer



TUBULAR L

Long spout 220 mm


- 350210 **TUBULAR LB**, 6 x 1.5 AA Batteries
- 350120 **TUBULAR LE**, 9V Transformer



TUBULAR 2030 L

Long spout 220 mm

- 350310 **TUBULAR 2030 LB**, 9V Battery
- 350410 **TUBULAR 2030 LE**, 9V Transformer




TUBULAR AISI316

Stainless steel 316 body

Concealed installation in dry walls

Iron frame available (see page 94)

- 350208 **TUBULAR B AISI316**, 6 x 1.5 AA Batteries
- 350109 **TUBULAR E AISI316**, 9V Transformer




TUBULAR 2030 AISI316

Stainless steel 316 body

Concealed installation in concrete or brick walls

Iron frame available (see page 94)


- 350402 **TUBULAR 2030E AISI316**, 9V Transformer



TUBULAR L AISI316

Long spout 220 mm


- 350213 **TUBULAR LB AISI316**, 6 x 1.5 AA Batteries
- 350124 **TUBULAR LE AISI316**, 9V Transformer



TUBULAR 2030 L AISI316

Long spout 220 mm

- 350412 **TUBULAR 2030LE AISI316**, 9V Transformer



TUBULAR XL

Concealed installation in dry walls

Extra long spout 295 mm



- 350215 **TUBULAR XLB**, 6 x 1.5 AA Batteries
- 350415 **TUBULAR XLE**, 9V Transformer

TUBULAR XL DP

Concealed installation in dry walls as well as concrete or brick walls

Dual power input box


- 350224 **TUBULAR XL DPB**, 9V Battery
- 350223 **TUBULAR XL DPE**, 9V Transformer



TUBULAR PERTH

Concealed installation in dry walls

- 350207 **TUBULAR PERTH B**, 6 x 1.5 AA Batteries
- 350107 **TUBULAR PERTH E**, 9V Transformer




TUBULAR 1000 AB1953

Concealed installation in dry walls

Mixer to adjust water temperature

- 350805 **TUBULAR 1000 B AB1953**, 6 x 1.5 AA Batteries
- 350855 **TUBULAR 1000 E AB1953**, 9V Transformer




TUBULAR 1000 BOX

Installation in concrete or brick walls

Mixer to adjust water temperature

- 350800 **TUBULAR 1000 B BOX**, 6 x 1.5 AA Batteries
- 350950 **TUBULAR 1000 E BOX**, 9V Transformer



TUBULAR 1000 L BOX

Long spout 220 mm

- 350910 **TUBULAR 1000 LB BOX**, 6 x 1.5 AA Batteries
- 350960 **TUBULAR 1000 LE BOX**, 9V Transformer






D28 SERIES


Electronic wall mounted faucet operated by IR sensor
For cold or premixed water.
Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.

WATER SAVING OPTIONS		
5 LPM	1.32 GPM	Honeycomb TT
1.89 LPM	0.5 GPM	PCA Spray



D28
Concealed installation in dry walls
Iron frame available (see page 94).

- 352000 **D28**, 9V Battery
- 352100 **D28 E**, 9V Transformer



D28 DUAL POWER
Concealed installation in dry walls as well as concrete or brick walls
Dual power input box

- 352300 **D28 DUAL POWER B**, 9V Battery
- 352400 **D28 DUAL POWER E**, 9V Transformer

When powered by a 9V transformer features an integrated backup system to be used with a 9V Lithium Battery, which enables the product to be used normally in case of a power failure. Iron Frame available (see page 94)


LONG SPOUT

D28 L
Long spout 275 mm

- 352010 **D28 LB**, 6 x 1.5 AA Batteries
- 352110 **D28 LE**, 9V Transformer


D28 DUAL POWER L
Long spout 275 mm

- 352303 **D28 DUAL POWER LB**, 9V Battery
- 352410 **D28 DUAL POWER LE**, 9V Transformer



D28 AISI316
Concealed installation in dry walls
Stainless steel 316 body

- 352130 **D28 AISI316**, 9V Battery
- 352120 **D28 E AISI316**, 9V Transformer



D28 DUAL POWER AISI316
Concealed installation in dry walls as well as concrete or brick walls
Stainless steel 316 body

- 352301 **D28 DPB AISI316**, 9V Battery
- 352401 **D28 DPE AISI316**, 9V Transformer

LONG SPOUT

D28 L AISI316
Long spout 275 mm

- 352015 **D28 LB AISI316**, 9V Battery
- 352125 **D28 LE AISI316**, 9V Transformer


D28 DP L AISI316
Long spout 275 mm

- 352304 **D28 DP LB AISI316**, 9V Battery
- 352403 **D28 DP LE AISI316**, 9V Transformer


CUBICA SERIES

Electronic wall mounted faucet operated by IR sensor
 The refined and geometrical series includes options for cold or premixed water with option of matching soap dispenser. Long spout models and various installation options.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray



- CUBICA**
 Concealed installation in plaster or dry wall
- 360100 **CUBICA B**, 9V Battery
 - 360200 **CUBICA E**, 9V Transformer




- CUBICA DP**
 Concealed installation in dry wall as well as concrete or brick wall
- 360110 **CUBICA DP B**, 9V Battery
 - 360210 **CUBICA DP E**, 9V Transformer




NARA Q SERIES

Electronic wall mounted faucet operated by IR sensor
 For cold or premixed water.
 Furthermore, this series includes a solenoid valve, located inside the product, which makes it more resistant to vandalism.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray



- NARA Q**
 Concealed installation in concrete or brick walls
- 360510 **NARA Q**, 9V Battery
 - 360500 **NARA QE**, 9V Transformer



MEDICAL SERIES


Electronic wall mounted faucet Operated by IR sensor
Features an integrated thermostatic mixer to prevent scalding operation and temperature control.
Furthermore, this series includes a solenoid valve, located inside the product, which makes it more resistant to vandalism.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




APOLLO MEDICAL F
Exposed installation
Gooseneck spout

- 314530 **APOLLO MEDICAL FB**,
Internal 9V Battery
- 314540 **APOLLO MEDICAL FE**,
9V Transformer





APOLLO MEDICAL
Exposed installation
Swivel spout

- 314500 **APOLLO MEDICAL B**,
Internal 9V Battery
- 314510 **APOLLO MEDICAL E**,
9V Transformer



MEDICAL 1000 T
Exposed installation
Body integrated spout

- 314600 **MEDICAL 1000 TE**,
9V Transformer




IR SENSOR:
a. Body recognition program
b. Sensor functions adjustable by remote control
c. Various hygiene flush options available



Remote Control
(Optional accessory)

Electronic wall mounted faucet operated by wave IR sensor
For cold or premixed water. Includes option for a longer bracket.

WATER SAVING OPTIONS		
6 LPM	1.58 GPM	SSR PCA Stream
4 LPM	1 GPM	PCA Spray
3 LPM	0.8 GPM	PCA Spray
1.89 LPM	0.5 GPM	PCA Spray
1.3 LPM	0.35 GPM	PCA Spray




Exposed installation
Allows activation of the faucet once the users place their hands at a close proximity to the sensor. Water will shut off if the users place their hands at a close proximity to the sensor - again or once a factory set flow time of 8 seconds will pass. The flow time is adjustable on site by remote control. With a mixer for water temperature adjustment for hot and cold water.

- 316010 **WASHFREE 1000**, 9V Battery
- **Long bracket 200 mm available upon request**

- Drastically reduces water consumption
- Non hold open feature
- More possibilities to save water: the water flow can be stopped in the middle of the cycle
- Stable and accurate water flow that can be changed on site



Touch-free prox sensor operation now available in a wide variety of special finishes to complete the interior design of your commercial restroom.



- Automatic Activation - The faucet turns on when users bring their hands within the sensor range.
- Instant Shut-Off - water stops automatically as soon as hands are removed.
- Detachable Sensor Body- designed for easy customization. Comes with an IP67-rated black battery box, powered by 6 AA 1.5V alkaline batteries.

- 620200 **PROX KIT WITH DETACHABLE BODY FOR FAUCET**
9V Battery / 9V Transformer




- The user waves their hand near the sensor a second time, or
- The pre-set flow time of 8 seconds elapses (factory default).

Flow time is fully adjustable on-site using a remote control.

- 620400 **WAVE KIT FOR FAUCET**, 9V Battery / 9V Transformer
- 620400 **WAVE KIT WITH DETACHABLE BODY FOR FAUCET**
9V Battery / 9V Transformer

- 07225008 **APS KIT FOR FAUCET**, 9V Battery / 9V Transformer (not included)





SOAP DISPENSERS



LOTUS TOPFILL

59-60



TUBULAR

75 - 78



BOREAL

61-62



EXTREME CS

79 - 80



CSABA

63 - 64



QUADRAT

81



TRENDY

65 - 66



CUBICA

82



EXTREME

67 - 68



MULTIFEED KITS

83 - 86



ELITE

69 - 70



PROPRIETARY SOAP ADAPTOR KITS

87



QUADRAT DM

71



SMARTBOX

88



CLASSIC

72



TOUCH FREE HAND SANITIZER STANDS

88-90



GREEN / GREEN 28

73 - 74

LOTUS TOPFILL E

An innovative deck-mounted soap dispenser for all types of liquid soap

The main features and benefits of the Lotus Top Fill:


- A 100% chrome-plated brass structure
- Delivers liquid/foam soap
- An enlarged 2 liter tank
- Peristaltic pump preventing back-flow and clogging
- A smart cap that enables easy filling from the top
- An LED soap level indicator that shows green if the container is full and red if empty.
- A variety of finishes: chrome, PVD brushed nickel, and matte black
- Matching touch-free faucet available
- Soap dosage and sensor range adjustable by remote control



2L



Pop-Top
Cap



LOTUS TOPFILL E

- 230850 LOTUS TOPFILL E, 12V Transformer
- 230860 LOTUS TOPFILL FE (FOAM), 12V Transformer

HIGH-TRAFFIC SOLUTION;

SOAP LEVEL INDICATOR (SLI)

Soap level indicator shows green when soap tank is full and red when the tank is empty

● Green blinks at maximum capacity ● Tank is empty



NEW!

BOREAL SOAP DISPENSER


Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

Features:

- Chrome plated brass body
- Delivers liquid/foam soap
- Peristaltic pump
- Adjustable settings



1L




BOREAL SOAP DISPENSER

- 212100 **BOREAL SOAP DISPENSER B**, Battery box for six (6) D batteries
- 212105 **BOREAL SOAP DISPENSER E**, 12V Transformer

BOREAL FOAM DISPENSER

- 212130 **BOREAL FD E**, 12V Transformer

TALL VERSION



BOREAL SOAP DISPENSER PLUS

Tall version: 210 mm body

- 212110 **BOREAL SD PLUS B**, Battery box for six (6) D batteries
- 212115 **BOREAL SD PLUS E**, 12V Transformer

BOREAL 6-PACK SOAP DISPENSER

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 212101 **BOREAL SD B 6-PACK**, Battery box for six (6) D batteries
- 212106 **BOREAL SD E 6-PACK**, 12V Transformer
- 212131 **BOREAL FD E 6-PACK**, 12V Transformer
- 212111 **BOREAL SD PLUS B 6-PACK**, Battery box for six (6) D batteries
- 212116 **BOREAL SD PLUS E 6-PACK**, 12V Transformer



CSABA SOAP DISPENSER

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:
- Chrome plated brass body / Stainless Steel AISI316 body
 - Concealed IR sensor integrated into the spout
 - Delivers liquid soap
 - Peristaltic pump

Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.




CSABA SOAP DISPENSER WITH SOAP LEVEL INDICATOR

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:
- Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty
 - Concealed IR sensor integrated into the spout
 - Delivers liquid soap
 - Peristaltic pump
 - 1.6 US gallon (6L) soap tank


1L



CSABA SOAP DISPENSER

- 233110 **CSABA SOAP DISPENSER B**, Battery box for six (6) D batteries
- 233100 **CSABA SOAP DISPENSER E**, 12V Transformer
- 233116 **CSABA SD B AISI316**, Battery box for six (6) D batteries
- 233130 **CSABA SD E AISI316**, 12V Transformer


TALL VERSION



CSABA SOAP DISPENSER PLUS


- Tall version: 302mm body
- 233114 **CSABA SD PLUS B**, Battery box for six (6) D batteries
 - 233106 **CSABA SD PLUS E**, 12V Transformer
 - 233117 **CSABA SD PLUS B AISI316**, Battery box for six (6) D batteries
 - 233108 **CSABA SD PLUS E AISI316**, 12V Transformer

6L



MF CSABA SOAP DISPENSER

- Deck-mounted touch-free electronic soap dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation
- 07292288 **MF CSABA SOAP DISPENSER**, 12V Transformer
 - 07292412 **MF CSABA SD AISI316**, 12V Transformer



CSABA SOAP DISPENSER WITH SOAP LEVEL INDICATOR

- 233105 **CSABA SOAP DISPENSER E WITH LEVEL INDICATOR**, 12V Transformer

CSABA 6-PACK SOAP DISPENSER

- Includes:
Six (6) liquid soap dispenser units
one (1) remote control
- 233111 **CSABA SD B 6-PACK**, Battery box for six (6) D batteries
 - 233101 **CSABA SD E 6-PACK**, 12V Transformer
 - 233115 **CSABA SD PLUS B 6-PACK**, Battery box for six (6) D batteries
 - 233107 **CSABA SD PLUS E 6-PACK**, 12V Transformer

CSABA 6-PACK SOAP DISPENSER AISI316

- Includes:
Six (6) liquid soap dispenser units
one (1) remote control
- 233118 **CSABA SD PLUS AISI316 B 6-PACK**, Battery box for six (6) D batteries
 - 233109 **CSABA SD PLUS E AISI316 6-PACK**, 12V Transformer

CSABA SD 1.6 E

- Delivers liquid soap
1.6 gallon (6L) tank kit for an individual soap dispenser
- 233102 **CSABA SD 1.6 E**, 12V Transformer



HIGH-TRAFFIC SOLUTION; SOAP LEVEL INDICATOR (SLI)

Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty.

- Tank is full
- Soap level is low
- Tank is empty

TRENDY SOAP DISPENSER

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:**
- Chrome plated brass body / Stainless Steel AISI316 body
 - Delivers liquid/foam soap
 - Peristaltic pump
 - Adjustable settings
 - Tall version

Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.




TRENDY SOAP DISPENSER WITH SOAP LEVEL INDICATOR

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:**
- Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty
 - Delivers liquid soap
 - Concealed IR sensor integrated into the spout
 - Peristaltic pump
 - 1.6 US gallon (6L) soap tank



1L




TRENDY SOAP DISPENSER

- 239910 **TRENDY SOAP DISPENSER B**, Battery box for six (6) D batteries
- 239900 **TRENDY SOAP DISPENSER E**, 12V Transformer
- 239905 **TRENDY SD B AISI316**, Battery box for six (6) D batteries
- 239904 **TRENDY SD E AISI316**, 12V Transformer

TRENDY FOAM DISPENSER

- 239930 **TRENDY FOAM E**, 12V Transformer

TALL VERSION




TRENDY SOAP DISPENSER PLUS

Tall version: 304mm body

- 239910 **TRENDY SOAP DISPENSER PLUS B**, Battery box for six (6) D batteries
- 239900 **TRENDY SOAP DISPENSER E PLUS**, 12V Transformer


6L



MF TRENDY SOAP DISPENSER

Deck-mounted touch-free electronic soap/foam dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation

- 07292073 **MF TRENDY SOAP DISPENSER**, 12V Transformer
- 07292273 **MF TRENDY SD AISI316**, 12V Transformer
- 07292183 **MF TRENDY FOAM DISPENSER**, 12V Transformer
- 07292418 **MF TRENDY FOAM AISI316**, 12V Transformer
- 07292099 **MF TRENDY SOAP DISPENSER PLUS**, 12V Transformer



TRENDY SOAP DISPENSER WITH LEVEL INDICATOR

- 239906 **TRENDY SOAP DISPENSER WITH LEVEL INDICATOR**, 12V Transformer

TRENDY 6-PACK SOAP DISPENSER

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 239911 **TRENDY SD B 6-PACK**, Battery box for six (6) D batteries
- 239901 **TRENDY SD E 6-PACK**, 12V Transformer
- 239931 **TRENDY FOAM E 6-PACK**, 12V Transformer
- 239913 **TRENDY SD PLUS B 6-PACK**, Battery box for six (6) D batteries
- 239903 **TRENDY SD PLUS E 6-PACK**, 12V Transformer

TRENDY 6-PACK SOAP DISPENSER AISI316


Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 239907 **TRENDY SD B AISI316 6-PACK**, Battery box for six (6) D batteries
- 239605 **TRENDY SD E AISI316 6-PACK**, 12V Transformer

TRENDY SD 1.6 E

1.6 gallon (6L) tank kit for an individual soap dispenser

- 239916 **TRENDY SD 1.6 E**, 12V Transformer



HIGH-TRAFFIC SOLUTION;

SOAP LEVEL INDICATOR (SLI)

Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty.

- Tank is full
- Soap level is low
- Tank is empty


EXTREME SOAP DISPENSER

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:**
- Chrome plated brass body
 - Delivers liquid soap
 - Peristaltic pump
 - Adjustable settings
 - Tall version



1L



EXTREME SOAP DISPENSER

- 237920 **EXTREME SOAP DISPENSER B**, Battery box for six (6) D batteries
- 237900 **EXTREME SOAP DISPENSER E**, 12V Transformer
- 237920 **EXTREME SOAP DISPENSER B**, Battery box for six (6) D batteries
- 237900 **EXTREME SOAP DISPENSER E**, 12V Transformer

EXTREME 6-PACK SOAP DISPENSER


Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 237921 **EXTREME SD B 6-PACK**, Battery box for six (6) D batteries
- 237901 **EXTREME SD E 6-PACK**, 12V Transformer
- 237923 **EXTREME SD PLUS B 6-PACK**, Battery box for six (6) D batteries
- 237906 **EXTREME SD PLUS E 6-PACK**, 12V Transformer


EXTREME SD 1.6 E

1.6 gallon (6L) tank kit for an individual soap dispenser

- 237916 **EXTREME SD 1.6 E**, 12V Transformer



TALL VERSION




EXTREME SOAP DISPENSER PLUS

Tall version: 304 mm body

- 237922 **EXTREME SOAP DISPENSER PLUS B**, Battery box for six (6) D batteries
- 237905 **EXTREME SOAP DISPENSER PLUS E**, 12V Transformer

6L



MF EXTREME SOAP DISPENSER


Deck-mounted touch-free electronic soap dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation

- 07292056 **MF EXTREME SOAP DISPENSER**, 12V Transformer
- 07292095 **MF EXTREME SOAP DISPENSER PLUS**, 12V Transformer

EXTREME SOAP DISPENSER WITH SOAP LEVEL INDICATOR

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:**
- Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty
 - Delivers liquid soap
 - Peristaltic pump
 - 1.6 US gallon (6L) soap tank



EXTREME SOAP DISPENSER WITH LEVEL INDICATOR

- 237917 **EXTREME SOAP DISPENSER WITH LEVEL INDICATOR**, 12V Transformer

HIGH-TRAFFIC SOLUTION;

SOAP LEVEL INDICATOR (SLI)

Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty.

- Tank is full
- Soap level is low
- Tank is empty

ELITE SOAP DISPENSER

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

Features:

- Chrome plated brass body / Stainless Steel AISI316 body
- Delivers liquid/foam soap
- Peristaltic pump
- Adjustable settings
- Tall version

Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.



ELITE SOAP DISPENSER WITH SOAP LEVEL INDICATOR


Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

Features:

- Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty
- Delivers liquid soap
- Peristaltic pump
- 1.6 US gallon (6L) soap tank




1L



- ELITE SOAP DISPENSER**
- 236110 **ELITE SOAP DISPENSER B**, Battery box for six (6) D batteries
 - 236100 **ELITE SOAP DISPENSER E**, 12V Transformer
 - 236113 **ELITE SOAP DISPENSER B AISI316**, Battery box for six (6) D batteries
 - 236103 **ELITE SOAP DISPENSER E AISI316**, 12V Transformer


- ELITE FOAM DISPENSER**
- 236120 **ELITE FOAM E**, 12V Transformer
 - 236122 **ELITE FOAM E AISI316**, 12V Transformer

TALL VERSION




- ELITE SOAP DISPENSER PLUS**
- Tall version: 304mm body
- 236107 **ELITE SOAP DISPENSER PLUS B**, Battery box for six (6) D batteries
 - 236105 **ELITE SOAP DISPENSER E PLUS**, 12V Transformer
 - 236109 **ELITE SOAP DISPENSER PLUS B AISI316**, Battery box for six (6) D batteries
 - 236104 **ELITE SOAP DISPENSER PLUS E AISI316**, 12V Transformer

6L



- MF ELITE SOAP DISPENSER**
- Deck-mounted touch-free electronic soap/foam dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation
- 07292077 **MF ELITE SOAP DISPENSER**, 12V Transformer
 - 07292205 **MF ELITE FOAM DISPENSER**, 12V Transformer
 - 07292093 **MF ELITE SOAP DISPENSER PLUS**, 12V Transformer
 - 07292239 **MF ELITE SOAP DISPENSER AISI316**, 12V Transformer
 - 07292240 **MF ELITE FOAM DISPENSER AISI316**, 12V Transformer
 - 07292241 **MF ELITE SOAP PLUS AISI316**, 12V Transformer



- ELITE SOAP DISPENSER WITH LEVEL INDICATOR**
- 236131 **ELITE SOAP DISPENSER WITH LEVEL INDICATOR**, 12V Transformer

- ELITE 6-PACK SOAP DISPENSER**
- Includes: Six (6) liquid soap dispenser units
One (1) remote control
- 236111 **ELITE SD B 6-PACK**, Battery box for six (6) D batteries
 - 236101 **ELITE SD E 6-PACK**, 12V Transformer
 - 236121 **ELITE FOAM E 6-PACK**, 12V Transformer
 - 236108 **ELITE SD PLUS B 6-PACK**, Battery box for six (6) D batteries
 - 236106 **ELITE SD PLUS E 6-PACK**, 12V Transformer

- 236114 **ELITE SD B 6-PACK AISI316**, Battery box for six (6) D batteries
- 236117 **ELITE SD E 6-PACK AISI316**, 12V Transformer
- 236123 **ELITE FOAM E 6-PACK AISI316**, 12V Transformer
- 236109 **ELITE SD PLUS B 6-PACK AISI316**, Battery box for six (6) D batteries
- 236104 **ELITE SD PLUS E 6-PACK AISI316**, 12V Transformer

- ELITE SD 1.6 E**
- 1.6 gallon (6L) tank kit for an individual soap dispenser
- 236216 **ELITE SD 1.6 E**, 12V Transformer
 - 236216 **ELITE SD 1.6 E AISI316**, 12V Transformer



HIGH-TRAFFIC SOLUTION; SOAP LEVEL INDICATOR (SLI)

Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty.

- Tank is full
- Soap level is low
- Tank is empty

QUADRAT DM SOAP DISPENSER


Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

Features:

- Chrome plated brass body
- Delivers liquid/foam soap
- Peristaltic pump
- Adjustable settings



1L



QUADRAT DM SOAP DISPENSER

- 351950 **QUADRAT DM SD B**, Battery box for six (6) D batteries
- 351952 **QUADRAT DM SD E**, 12V Transformer
- 351960 **QUADRAT DM FOAM E**, 12V Transformer

QUADRAT DM 6-PACK SOAP DISPENSER

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 351951 **QUADRAT DM SD B 6-PACK**, Battery box for six (6) D batteries
- 351953 **QUADRAT DM SD E 6-PACK**, 12V Transformer
- 351961 **QUADRAT DM FOAM E 6-PACK**, 12V Transformer

CLASSIC SOAP DISPENSER


Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

Features:

- Chrome plated brass body
- Delivers liquid/foam soap
- Peristaltic pump
- Concealed IR sensor integrated into the spout
- Adjustable settings



1L




CLASSIC SOAP DISPENSER

- 292400 **CLASSIC SOAP DISPENSER B**, Battery box for six (6) D batteries
- 292410 **CLASSIC SOAP DISPENSER E**, 12V Transformer

CLASSIC FOAM DISPENSER

- 292300 **CLASSIC FOAM E**, 12V Transformer

6L



MF CLASSIC SOAP DISPENSER

Deck-mounted touch-free electronic soap/foam dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation

- 07292177 **MF CLASSIC SOAP DISPENSER**, 12V Transformer
- 07292207 **MF CLASSIC FOAM DISPENSER**, 12V Transformer

CLASSIC 6-PACK SOAP DISPENSER

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 292401 **CLASSIC SD B 6-PACK**, Battery box for six (6) D batteries
- 292411 **CLASSIC SD E 6-PACK**, 12V Transformer
- 292301 **CLASSIC FOAM E 6-PACK**, 12V Transformer

CLASSIC SD 1.6 E

1.6 gallon (6L) tank kit for an individual soap dispenser

- 292416 **CLASSIC SD 1.6 E**, 12V Transformer




GREEN SOAP DISPENSER

Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:**
- Chrome plated brass body
 - Delivers liquid/foam soap
 - Peristaltic pump
 - Adjustable settings
 - Includes a brass base for extra protection in high traffic locations



1L




GREEN SOAP DISPENSER

- 225845 **GREEN SOAP DISPENSER B**, Battery box for six (6) D batteries
- 225840 **GREEN SOAP DISPENSER E**, 12V Transformer

GREEN FOAM DISPENSER

- 225842 **GREEN FOAM E**, 12V Transformer

6L



MF GREEN SOAP DISPENSER

- Deck-mounted touch-free electronic soap/foam dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation
- 07292062 **MF GREEN SOAP DISPENSER**, 12V Transformer
 - 07292228 **MF GREEN FOAM DISPENSER**, 12V Transformer



GREEN 6-PACK SOAP DISPENSER

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 225846 **GREEN SD B 6-PACK**, Battery box for six (6) D batteries
- 225841 **GREEN SD E 6-PACK**, 12V Transformer
- 225843 **GREEN FOAM E 6-PACK**, 12V Transformer

GREEN SD 1.6 E

1.6 gallon (6L) tank kit for an individual soap dispenser

- 225816 **GREEN SD 1.6 E**, 12V Transformer



GREEN 28 SOAP DISPENSER


Deck-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:**
- Chrome plated brass body
 - Delivers liquid/foam soap
 - Peristaltic pump
 - Adjustable settings
 - Includes a brass base for extra protection in high traffic locations

Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.



1L



GREEN 28 SOAP DISPENSER

- 352900 **GREEN 28 SOAP DISPENSER B**, Battery box for six (6) D batteries
- 352910 **GREEN 28 SOAP DISPENSER E**, 12V Transformer

GREEN 28 SOAP DISPENSER AISI 316

- 352912 **GREEN 28 SD E AISI316**, 12V Transformer


GREEN 28 FOAM DISPENSER

- 352920 **GREEN 28 FOAM E**, 12V Transformer

GREEN 28 FOAM DISPENSER AISI 316

- 352922 **GREEN 28 FD E**, 12V Transformer

6L



MF GREEN 28 SOAP DISPENSER

- Deck-mounted touch-free electronic soap/foam dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation
- 07292155 **MF GREEN 28 SOAP DISPENSER**, 12V Transformer
 - 07292206 **MF GREEN F28 FOAM DISPENSER**, 12V Transformer

GREEN 6-PACK SOAP DISPENSER

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 352901 **GREEN 28 SD B 6-PACK**, Battery box for six (6) D batteries
- 352911 **GREEN 28 SD E 6-PACK**, 12V Transformer
- 352921 **GREEN 28 FOAM E 6-PACK**, 12V Transformer

GREEN 28 SD 1.6 E

1.6 gallon (6L) tank kit for an individual soap dispenser


- 352916 **GREEN 28 SD 1.6 E**, 12V Transformer




TUBULAR SOAP DISPENSER

Wall-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:
- Chrome plated brass body
 - Delivers liquid/foam soap
 - Peristaltic pump
 - Adjustable settings



1L



TUBULAR SOAP DISPENSER

Installation in dry walls
Optional version: 120mm


- 350920 **TUBULAR SOAP DISPENSER B**, Battery box for six (6) D batteries
- 350925 **TUBULAR SOAP DISPENSER E**, 12V Transformer

TUBULAR FOAM DISPENSER

Optional version: 120mm

- 350980 **TUBULAR FOAM E**, 12V Transformer

6L




MF TUBULAR SOAP DISPENSER

Wall-mounted touch-free electronic soap dispenser to be used with Stern's Multifeed kits for multiple soap dispensers installation
Installation in dry walls
Optional version: 120mm

- 07292076 **MF TUBULAR SOAP DISPENSER**, 12V Transformer
- 07292186 **MF TUBULAR FOAM DISPENSER**, 12V Transformer

1L



TUBULAR SOAP DISPENSER AISI316


Wall-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:**
- Stainless Steel AISI316 product body
 - Delivers liquid/foam soap
 - Peristaltic pump
 - Adjustable settings

Comes in Stainless steel AISI 316 and other customized finishes to match all design concepts.



1L



TUBULAR SOAP DISPENSER AISI316

Installation in dry walls
Optional version: 120mm


- 350919 **TUBULAR SOAP DISPENSER AISI316 B**, Battery box for six (6) D batteries
- 350924 **TUBULAR SOAP DISPENSER AISI316 E**, 12V Transformer

TUBULAR FOAM DISPENSER AISI316

Installation in dry walls

- 350982 **TUBULAR FOAM E AISI316**, 12V Transformer

6L



MF TUBULAR SOAP DISPENSER AISI316


To be used with Stern's Multifeed kits for multiple soap dispensers installation

Installation in dry walls

Optional version: 120mm

- 07292221 **MF TUBULAR SOAP DISPENSER AISI316**, 12V Transformer
- 07292231 **MF TUBULAR FOAM DISPENSER AISI316**, 12V Transformer

1L




TUBULAR SOAP DISPENSER 2030 AISI316

Concealed installation in concrete or brick walls

Optional version: 120mm

- 350918 **TUBULAR SD 2030 B AISI316**, Battery box for six (6) D batteries
- 350917 **TUBULAR SD 2030 E AISI316**, 12V Transformer

6L



MF TUBULAR SOAP DISPENSER 2030 AISI316

To be used with Stern's Multifeed kits for multiple soap dispensers installation

Concealed installation in concrete or brick walls

Optional version: 120mm

- 07292222 **MF TUBULAR SOAP DISPENSER 2030 AISI316**, 12V Transformer



TUBULAR SD AISI 316 6-PACK

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 350991 **TUBULAR SD AISI 316 B 6-PACK**, Battery box for six (6) D batteries
- 350984 **TUBULAR SD AISI 316 E 6-PACK**, 12V Transformer
- 350983 **TUBULAR FOAM E AISI 316 6-PACK**, 12V Transformer

TUBULAR SD 1.6 E AISI 316

1.6 gallon (6L) tank kit for an individual soap dispenser

- 350932 **TUBULAR SD 1.6 E AISI 316**, 12V Transformer



TUBULAR 2030 6-PACK SOAP DISPENSER AISI 316

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 350992 **TUBULAR SD 2030B AISI316 6-PACK**, Battery box for six (6) D batteries
- 350933 **TUBULAR SD 2030E AISI316 6-PACK**, 12V Transformer

TUBULAR 2030 SD 1.6 E AISI 316

1.6 gallon (6L) tank kit for an individual soap dispenser

- 350916 **TUBULAR 2030 SD 1.6 E AISI316**, 12V Transformer



EXTREME CS SOAP DISPENSER

Wall-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:
- Concealed sensor integrated into the spout
 - Delivers liquid soap
 - Peristaltic pump
 - Adjustable settings
 - Stainless steel AISI316 spout available



STAINLESS
STEEL
AISI316
OPTION


1L



EXTREME CS SOAP DISPENSER

Installation in dry walls


- 237891 **EXTREME CS SOAP DISPENSER B**, Battery box for six (6) D batteries
- 237890 **EXTREME CS SOAP DISPENSER E**, 12V Transformer



EXTREME CS SD 2030

Concealed installation in concrete or brick walls

- 237896 **EXTREME CS SD 2030 B**, Battery box for six (6) D batteries
- 237892 **EXTREME CS SD 2030 E**, 12V Transformer



6L




MF EXTREME CS SOAP DISPENSER

To be used with Stern's Multifeed kits for multiple soap dispensers installation

Installation in dry walls

- 07292271 **MF EXTREME CS SD E**, 12V Transformer




MF EXTREME CS SD 2030

To be used with Stern's Multifeed kits for multiple soap dispensers installation

Concealed installation in concrete or brick walls

- 07292290 **MF EXTREME SOAP DISPENSER 2030**, 12V Transformer




1L



EXTREME CS SOAP DISPENSER AISI316

Installation in dry walls


- 237891-316 **EXTREME CS SOAP DISPENSER B AISI316**, Battery box for six (6) D batteries
- 237890-316 **EXTREME CS SOAP DISPENSER E AISI316**, 12V Transformer



EXTREME CS SD 2030 AISI316

Concealed installation in concrete or brick walls

- 237896-316 **EXTREME CS SD 2030 B AISI316**, Battery box for six (6) D batteries
- 237892-316 **EXTREME CS SD 2030 E AISI316**, 12V Transformer



6L




MF EXTREME CS SD AISI316

To be used with Stern's Multifeed kits for multiple soap dispensers installation

Installation in dry walls

- 07292285 **MF EXTREME CS SD E AISI316**, 12V Transformer




MF EXTREME CS SD 2030 AISI316

To be used with Stern's Multifeed kits for multiple soap dispensers installation

Concealed installation in concrete or brick walls

- 07292286 **MF EXTREME SD 2030 AISI316**, 12V Transformer



EXTREME CS 6-PACK SOAP DISPENSER


Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 237894 **EXTREME CS SD B 6-PACK**, Battery box for six (6) D batteries
- 237893 **EXTREME CS SD E 6-PACK**, 12V Transformer
- 237897 **EXTREME CS 2030 SD B 6-PACK**, Battery box for six (6) D batteries
- 237895 **EXTREME CS 2030 SD E 6-PACK**, 12V Transformer

EXTREME CS SD 1.6 E

1.6 gallon (6L) tank kit for an individual soap dispenser

- 237882 **EXTREME CS SD 1.6 E**, 12V Transformer
- 237884 **EXTREME CS 2030 SD 1.6 E**, 12V Transformer



EXTREME CS AISI316 6-PACK SOAP DISPENSER

Includes: Six (6) liquid soap dispenser units
One (1) remote control

- 237898 **EXTREME CS SD B AISI316 6-PACK**, Battery box for six (6) D batteries
- 237899 **EXTREME CS SD E AISI316**, 12V Transformer
- 237880 **EXTREME CS SD 2030 B AISI316 6-PACK**, Battery box for six (6) D batteries
- 237881 **EXTREME CS SD 2030E AISI316 6-PACK**, 12V Transformer

EXTREME CS SD AISI316 1.6 E

1.6 gallon (6L) tank kit for an individual soap dispenser

- 237885 **EXTREME CS SD AISI316 1.6 E**, 12V Transformer
- 237883 **EXTREME CS 2030 SD AISI316 1.6 E**, 12V Transformer



QUADRAT SOAP DISPENSER

Wall-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:
- 100% heavy-duty one piece brass body
 - Delivers liquid soap
 - Chrome plated brass body
 - Peristaltic pump
 - Adjustable settings




CUBICA SOAP DISPENSER

Wall-mounted touch-free electronic soap dispenser for non-proprietary soap

- Features:
- 100% heavy-duty one piece brass body
 - Delivers liquid soap
 - Chrome plated brass body
 - Peristaltic pump
 - Adjustable settings



1L




QUADRAT SOAP DISPENSER


- Installation in dry walls
- 351910 **QUADRAT SOAP DISPENSER B**, Battery box for six (6) D batteries
 - 351900 **QUADRAT SOAP DISPENSER E**, 12V Transformer

QUADRAT SOAP DISPENSER 2030

- Concealed installation in concrete or brick walls
- 351920 **QUADRAT SOAP DISPENSER 2030 B**, Battery box for six (6) D batteries
 - 351930 **QUADRAT SOAP DISPENSER 2030 E**, 12V Transformer



6L




MF QUADRAT SOAP DISPENSER


- To be used with Stern's Multifeed kits for multiple soap dispensers installation
- Installation in dry walls
- 07292078 **MF QUADRAT SOAP DISPENSER**, 12V Transformer

MF QUADRAT SOAP DISPENSER 2030

- To be used with Stern's Multifeed kits for multiple soap dispensers installation
- Concealed installation in concrete or brick walls
- 07292094 **MF QUADRAT SOAP DISPENSER 2030**, 12V Transformer



1L




CUBICA SOAP DISPENSER


- Installation in dry walls
- 360620 **CUBICA SOAP DISPENSER B**, Battery box for six (6) D batteries
 - 360630 **CUBICA SOAP DISPENSER E**, 12V Transformer

CUBICA SOAP DISPENSER 2030

- Concealed installation in concrete or brick walls
- 360600 **CUBICA SOAP DISPENSER 2030 B**, Battery box for six (6) D batteries
 - 360610 **CUBICA SOAP DISPENSER 2030 E**, 12V Transformer



6L



MF CUBICA SOAP DISPENSER

- To be used with Stern's Multifeed kits for multiple soap dispensers installation
- Installation in dry walls
- 07292396 **MF CUBICA SOAP DISPENSER**, 12V Transformer
 - 07292426 **MF CUBICA SD 2030**, 12V Transformer

QUADRAT SD 6-PACK SOAP DISPENSER

- Includes: Six (6) liquid soap dispenser units
One (1) remote control
- 351911 **QUADRAT SD B 6-PACK**, Battery box for six (6) D batteries
 - 351901 **QUADRAT SD E 6-PACK**, 12V Transformer
 - 351921 **QUADRAT 2030 SD B 6-PACK**, Battery box for six (6) D batteries
 - 351931 **QUADRAT 2030 SD E 6-PACK**, 12V Transformer

QUADRAT SD 1.6 E

- 1.6 gallon (6L) tank kit for an individual soap dispenser
- 351916 **QUADRAT SD 1.6 E**, 12V Transformer
 - 351316 **QUADRAT 2030 SD 1.6 E**, 12V Transformer



CUBICA SD 6-PACK SOAP DISPENSER

- Includes: Six (6) liquid soap dispenser units
One (1) remote control
- 360621 **CUBICA SD B 6-PACK**, Battery box for six (6) D batteries
 - 360631 **CUBICA SD E 6-PACK**, 12V Transformer
 - 360601 **CUBICA 2030 SD B 6-PACK**, Battery box for six (6) D batteries
 - 360611 **CUBICA 2030 SD E 6-PACK**, 12V Transformer

CUBICA SD 1.6 E

- 1.6 gallon (6L) tank kit for an individual soap dispenser
- 360622 **CUBICA SD 1.6 E**, 12V Transformer
 - 360612 **CUBICA 2030 SD 1.6 E**, 12V Transformer



MULTIFEED KITS

Installation kit for more efficient maintenance of multiple soap dispensers. Saves time and money, and can supply up to six soap dispensers from one large capacity 1.6 gallon (6L) soap tank. Ideal for high traffic areas with multiple hand washing stations in high traffic restrooms. Enables productive refill of multiple soap dispensers through a single top fill unit above deck and an LED indicator that lets maintenance staff know when soap levels are low. Suitable for any foam or liquid soap with the recommended viscosity.

Features:


- Allows multiple soap dispensers installation (up to six (6) dispensers) with a single 1.6 US gallon (6L) soap tank.
- Stainless Steel tank support or lockable underbasin cabinet

Options:

- Anti-theft top filling brass mechanism for easy refill from the counter top
- Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty
- Below deck filling mechanism
- **NEW:** Plywood HPL (High Pressure Laminate) lockable cabinet with level indicator window. White panel and oak style frame for 1.6 Gallon (6L) soap tank with option to house the 33.8 FL OZ (1L) soap bottle as necessary. Hides unsightly pipes and connectors from the view of users.



Advantages:

- Drastically reduces soap consumption
- Cross contamination protection - no physical contact
- Maximized savings - can be used with any non-proprietary soap
- Easy installation
- Fast and simple refill with optional LED indication of soap level
- Highly durable - with optional vandal-resistant top-filling mechanism



TOP-FILLING MULTIFEED KIT WITH SOAP LEVEL INDICATOR

Vandal-resistant chrome-plated top-filling brass mechanism. LED soap level indicator.
Power splitter for connection to transformer powered MF soap dispenser.
Stainless steel tank support.




• 07220152
Top-Filling Multifeed Kit with Soap Level Indicator

HIGH-TRAFFIC SOLUTION; SOAP LEVEL INDICATOR (SLI)

Soap level indicator shows green when soap tank is full, orange when soap level is low, and red when the tank is empty.

- Tank is full ● Soap level is low ● Tank is empty



• 07220152CB
Top-Filling Multifeed Kit with Soap Level Indicator and lockable cabinet

TOP-FILLING MULTIFEED KIT


Vandal-resistant chrome-plated top-filling brass mechanism.

Available for transformer powered MF soap dispensers.


With lockable cabinet.



• 07220090
Top-Filling Multifeed Kit



• 07220090CB
Top-Filling Multifeed With lockable cabinet



BELOW DECK MULTIFEED KIT


Vandal-resistant chrome-plated top-filling brass mechanism.

Available for transformer powered MF soap dispensers.



With lockable cabinet.



• 07220096
Below Deck Multifeed Kit



• 07220096CB
Below Deck Multifeed Kit With lockable cabinet



PROPRIETARY SOAP ADAPTOR KITS

Just choose the adaptor that fits your soap container and fit it to the opening of your choice of soap container. Insert the pipe into the hole in the cap, attach the quick connector to the pipe, and voilà! Your Stern soap dispenser is ready to use your selected soap.

Ordering information at page 137



Kit contains:

Adaptor



Quick connector



2-3 way Quick connector (Optional)




Pipe cutter



Pipe x 1






Option to connect up to 3 soap dispensers




GREAT FOR
HI-TRAFFIC
PROJECTS



SMARTBOX 2LE

Touch-free hand sanitizer dispenser for wall-mounted installations
Activated by an infrared sensor located in the base. For use with any non-proprietary hand sanitizer gel of the recommended viscosity.

- Features:**
- Stainless Steel AISI 316 body
 - Delivers non-proprietary hand sanitizer
 - Peristaltic pump
 - Adjustable settings



2L

- SMARTBOX 2L**
- 280222 **SMARTBOX 2LE**, 12V Transformer



TOUCH FREE HAND SANITIZER


Touch-free electronic hand sanitizer stand for deck-mounted installations with dripless automatic shutoff. Suitable for supermarkets, banks, lobbies and any high traffic public areas.

Features:

- 100% heavy-duty one piece brass body
- Delivers non-proprietary hand sanitizer
- Chrome plated brass body dispenser
- Power Supply: Battery box for six (6) D batteries or 12V transformer
- Peristaltic pump
- Adjustable settings


PILLAR - 1L

- 281100CSB **CSABA TOUCH FREE HAND SANITIZER PILLAR 1L**
Battery box for six (6) D batteries
- 281100CSE **CSABA TOUCH FREE HAND SANITIZER PILLAR 1L**
12V Transformer




STAND - 1L

- 281000CS1B **CSABA TOUCH FREE HAND SANITIZER STAND 1L**
Battery box for six (6) D batteries
- 281000CS1E **CSABA TOUCH FREE HAND SANITIZER STAND 1L**
12V Transformer



STAND - 6L


- 281000CS6B **CSABA TOUCH FREE HAND SANITIZER STAND 6L**
Battery box for six (6) D batteries
- 281000CS6E **CSABA TOUCH FREE HAND SANITIZER STAND 6L**
12V Transformer



STATION - 6L

- 233200 **CSABA WM HAND SANITIZER STATION**
Battery box for six (6) D batteries /12V Transformer






IRON FRAME SETS

	SOAP, WATER & AIR FRAME SETS	93 - 94
	W.C. FRAME SETS	95 - 96
	ARTIS H CISTERN FRAME SET	97
	URINALS FRAME SETS	98

SOAP, WATER, & AIR FRAME SETS

Iron mounting frame set


Touch-free soap dispenser, touch-free faucet, and hi-speed hand dryer for public bathroom use. Operated by IR sensor. The system includes mounting support for the washbasin, faucet, soap dispenser, and hand dryer, available with full brass body or AISI316 material.



TUBULAR TRIO DP KE W/BASIN

12V Transformer and power splitter


- 500130 TUBULAR TRIO DP KE W/BASIN
- Includes DuPont Corian washbasin and mounting support for the washbasin, faucet, soap dispenser and hand dryer.



TUBULAR DP TRIO KE

12V Transformer and power splitter



- 500120 TUBULAR DP TRIO KE



D28 DP SOAP&WATER KE

12V Transformer and power splitter


- 500100 D28 DP SOAP&WATER KE



TUBULAR DP SOAP&WATER KE

12V Transformer and power splitter


- 500200 TUBULAR DP SOAP&WATER KE



CUBICA DP SOAP & WATER KE

12V Transformer and power splitter


- 500530 CUBICA DP SOAP & WATER KE



MALMO 1000 DP SOAP&WATER KE

12V Transformer and power splitter

- 500350 MALMO 1000 DP SOAP&WATER KE



EXTREME CS SOAP & WATER KE

12V Transformer and power splitter

- 500500 EXTREME CS SOAP & WATER KE,
- 500510 EXTREME CS SOAP & WATER KE AISI316



W.C. FRAME SETS

Electronic WC Frame Set

Galvanized steel iron frame system for wall hang toilets. For concrete or dry walls with four (4) steel screws. Delivered ready for installation with flush valve and complete required accessories included.

* Toilet bowl not included

Dual flush: The sensor controls the flushing according to the time the user spends within the sensor range. If the user spends less then one (1) minute within the sensor range a reduced 3 liters flush will take place. If the user spends one (1) minute or more within the sensor range a full 6 liters flush will take place.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.




W.C. FRAME SETS

Iron mounting frame set

Galvanized steel iron frame system for wall hang toilets. Delivered ready for installation with flush valve and complete required accessories included. Options for touch or touch-free operation.


* Toilet bowl not included

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



NOBLE 2032 KE
Dual flush
Features a manual override flush activator button

- 800320 **NOBLE 2032 KE**, 9V Transformer




NARA 2032 K
Dual flush
Features a manual override flush activator button

- 800271 **NARA 2032 K**, 9V Battery
- 800276 **NARA 2032 KE**, 9V Transformer




NARA 2032 PK
Dual flush
Features touch override flush piezo button

- 800287 **NARA 2032 PK**, 9V Battery
- 800279 **NARA 2032 PKE**, 9V Transformer



VENUS COMFORT 2032 DF K
Features two Piezo flush activator switches for each flush volume

- 800221 **VENUS COMFORT 2032 DF K**, 9V Battery
- 800236 **VENUS COMFORT 2032 DF KE**, 9V Transformer



PERFECT TIME 2032K
Operated by a piezo switch integrated in the panel


- 800286 **PERFECT TIME 2032KE**, 9V Battery

ARTIS H

Electronic touch-free concealed cistern system

Complete with an iron frame for wall hung toilet. Activated by a dual flush infrared sensor. Operated by an IP68 encapsulated switching adapter 12V transformer. Includes an override touch piezo switch, and an integral overflow pipe (warning pipe) to prevent flooding. Stainless steel AISI316 panel and 2 vandal resistant side screws, other finishes available. Pre-flush optional upon request. A 24 hour hygiene flush is included. The following settings can be changed by using the Stern remote control: Sensor Range, Security Time, Delay In, Delay Out, and On-Off.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



ARTIS H
Dual flush operation.
Includes an override touch piezo switch.

- 800420 **ARTIS H**, 9V Transformer


URINALS FRAME SETS

Iron mounting frame set

Delivered ready for installation with flush valve and complete required accessories included.
* Urinal bowl not included




Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



NARA 2030 K

- 800277 **NARA 2030 K**, 9V Battery
- 800278 **NARA 2030 KE**, 9V Transformer



JUPITER 2040 K

- 800241 **JUPITER 2040 K**, 9V Battery
- 800251 **JUPITER 2040 KE**, 9V Transformer



TOILETS & URINALS

	NOBLE 2032	101		PROX, WAVE & TOUCH SOLUTIONS FOR TOILET	110
	NOBLE 3032	102		PROX & WAVE SENSOR KIT FOR TOILET	110
	NARA 2032 NARA 2022	103 - 105		JUPITER 2040	111
	VENUS XS 2032	106		NARA 2030	112
	VENUS COMFORT 2032 DF	107		FREE	113-114
	PERFECT TIME 2032	107		JUPITER 3002	115
	VENUS 3002	108		PROX FOR URINALS	116
	APS KIT FOR TOILETS WITH DISTANT CONTROL	109			


NOBLE 2032 SERIES

Concealed electronic flush valve for toilet, operated by an IR sensor
Features a dual flush IR system. Includes models with a Piezo override flush activator switch giving the user the possibility of alternative manual touch activation. Flushing duration and other settings are adjustable by remote control. Stainless steel AISI316 panel.


Dual flush: Water will flush after the user moves away from the toilet. If the user spends less than one minute in front of the sensor a half flush (3 liters) will take place. For more than one minute in front of the sensor a full flush (4.5 liters) will take place.

* default for the is 3 liters and 4.5 liters instead of 3 liter and 6 liters.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



- NOBLE 2032**
Dual flush operation
With a mechanical override flush button
Iron frame available
- 460640 **NOBLE 2032**, 9V battery
 - 460600 **NOBLE 2032 E**, 9V Transformer




- NOBLE 2032 P**
Dual flush operation
With a a touch flush activator button
- 460630 **NOBLE 2032 P**, 9V battery
 - 460610 **NOBLE 2032 PE**, 9V Transformer

NOBLE 3032 SERIES


Concealed electronic flush valve for toilet, operated by an IR sensor
Features a dual flush IR system. Includes models with a Piezo override flush activator switch giving the user the possibility of alternative manual touch activation. Flushing duration and other settings are adjustable by remote control. Stainless steel AISI316 panel.

Dual flush: Water will flush after the user moves away from the toilet. If the user spends less than one minute in front of the sensor a half flush (3 liters) will take place. For more than one minute in front of the sensor a full flush (6 liters) will take place.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



- NOBLE 3032**
Dual flush
A half flush (3 liters) will take place. For more than one minute, a full flush (6 liters) will take place
Manual override push button anti-block feature
Iron frame available
- 460700 **NOBLE 3032**, 6 x 1.5V batteries
 - 460710 **NOBLE 3032 E**, 9V Transformer



- NOBLE 3032 P**
Dual flush
A half flush (3 liters) will take place. For more than one minute, a full flush (6 liters) will take place
Piezo override push button anti-block feature
Iron frame available
- 460720 **NOBLE 3032 P**, 6 x 1.5V batteries
 - 460730 **NOBLE 3032 PE**, 9V Transformer


NARA 2032 SERIES

Concealed electronic flush valve for toilet operated by IR sensor
Features a dual flush IR system

Includes models with a Piezo override flush activator switch giving the user the possibility of alternative manual touch activation. Flushing duration and other settings are adjustable by remote control.

Dual flush: Water will flush after the user moves away from the toilet. If the user spends less than one minute in front of the sensor, a half flush (3 liters) will take place. For more than one minute, a full flush (6 liters) will take place.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



NARA 2032

Dual flush

A half flush (3 liters) will take place. For more than one minute, a full flush (6liters) will take place.

Features a mechanical override flush activator button

Iron frame available. See also page 137

- 160310 **NARA 2032** , 9V Battery
- 160410 **NARA 2032 E**, 9V Transformer

NARA ECO 2032

Dual flush

A half flush (3 liters) will take place. For more than one minute, a Leed full flush (4.5 liters) will take place.

Features a mechanical override flush activator button

Iron frame available. See also page 137

- 160320 **NARA ECO 2032** , 9V battery
- 160330 **NARA ECO 2032 E**, 9V Transformer

NARA 2032 P

Dual flush

A half flush (3 liters) will take place. For more than one minute, a full flush (6liters) will take place.

Features a touch flush activator button

Iron frame available. See also page 137

- 160610 **NARA 2032 P**, 9V Battery
- 160510 **NARA 2032 PE**, 9V Transformer

NARA ECO 2032 P


Dual flush

A half flush (3 liters) will take place. For more than one minute, a Leed full flush (4.5 liters) will take place.

Features a touch flush activator button

Iron frame available. See also page 137

- 160340 **NARA ECO 2032 PE**, 9V Transformer




NARA 2022 SERIES

Concealed electronic flush valve for toilet operated by IR sensor
Features a dual flush IR system

Includes models with a Piezo override flush activator switch giving the user the possibility of alternative manual touch activation. Flushing duration and other settings are adjustable by remote control.

Dual flush: Water will flush after the user moves away from the toilet. If the user spends less than one minute in front of the sensor, a half flush (3 liters) will take place. For more than one minute, a full flush (6 liters) will take place.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.




NARA 2022

Dual flush

A half flush (3 liters) will take place. For more than one minute, a full flush (6liters) will take place.

Features an hydraulic override flush activator button


- 160750 **NARA 2022**, 9V Battery
- 160700 **NARA 2022 E**, 9V Transformer



ACCESSORIES

- 07291037 **SET OF PIPES**
Set of pipes for in wall installation






VENUS XS 2032

Concealed electronic flush valve for toilet operated by IR sensor

Dual flush IR system upon request. Includes models with a Piezo override flush activator switch, giving the user the possibility of alternative flushing with an easy touch activation. Flushing duration and other settings are adjustable by remote control.

The panels are secured with vandal-resistant screws for added protection.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



VENUS XS 2032


Features a manual override flush activator button
Optional dual flush

- 410601 **VENUS XS 2032E**, 9V Transformer

APS KIT FOR TOILETS WITH DISTANT CONTROL

Electronically operated self closing flush valve for toilet with distant control

Designated for special needs or high security locations. Can be operated by a Piezo button located in the toilet area, or using the remote panel for alternative operation. Each activation gives a pre-set run cycle.



PIEZO KIT FOR W.C. WITH DISTANT CONTROL

Suitable for duct concealed installations (plaster walls)

Default Special needs version:

Includes a BPS Piezo switch to be installed in the toilet area for standard operation and a remote panel to be installed in a remote location for an alternative easy activation.

Suitable for duct concealed installations (plaster walls)

Optional High security version:

Includes a BPS switch located in the inmate's cell that allows to flush the toilet, while the flush valve body is concealed in the service area. The remote panel, installed outside the cell, allows disabling the system to perform sudden search procedures for drugs or weapons. Includes a Red ring of light indication when the system is disabled. Once disabled, the system can be enabled manually by the prison personnel or automatically after one hour.

- 07226042 **PIEZO KIT FOR W.C. WITH DISTANT CONTROL**, 9V Transformer

PROX, WAVE & TOUCH SOLUTIONS


Touch free & Touch operated flush valve for toilet kits

Electronic modular flush valve for toilet for installation in the wall or panel. Flushing duration and other settings are adjustable by remote control.

PROX & WAVE SENSOR KIT FOR TOILET WITH PRIMARY FLUSH

This kit is designed to operate a two volumes flush valve. The sensor detects the user at a given distance, and operates an automatic flush using the sensor's prox function once the user has left the toilet. Depending on time and distance, the systems delivers 3 liters to evacuate liquids and 6 liters to evacuate solids.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



PROX / WAVE KIT FOR TOILETS


Suitable for duct concealed installations (plaster walls)

Available with detachable body

Touch free Operation

Allows automatic activation when the users have left the toilet.

- 620100 **PROX KIT FOR TOILETS**, 9V Transformer / 9V battery (not included)
- 620600 **WAVE ON/OFF SENSOR KIT FOR TOILET**, 9V Transformer / 9V battery (not included)




APS KIT FOR TOILETS

Suitable for duct concealed installations (plaster walls)

Touch Operation

Allows activation of the toilet once the users touch the designated area in the Piezo button.

- 07225018 **APS KIT FOR TOILETS**, 9V Transformer / 9V battery (not included)



PROX & WAVE SENSOR KIT FOR TOILET

Suitable for duct concealed installations (plaster walls).

Primary cleaning flush

Allows the user to operate a cleaning flush before using the system.

The 3 liters flush takes places when the user presents his hand at a short distance at the front of the sensor.

Dual Flush

The system will operate a half flush (3 liters) or a full flush (6 liters) based on a time and distance equation.


- 620100 -Prox/Wave **PROX & WAVE SENSOR KIT FOR TOILET**, 9V Battery / 9V Transformer (not included)



JUPITER 2040 SERIES

Concealed electronic flush valve for urinal operated by IR sensor
 Flushing duration and other settings are adjustable by remote control.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.




- JUPITER 2040**
 Iron frame available. See also page 139
- 125900 **JUPITER 2040** , Internal 9V battery
 - 125901 **JUPITER 2040 E**, 9V Transformer



NARA 2030 SERIES

Concealed electronic flush valve for urinal operated by IR sensor
 Flushing duration and other settings are adjustable by remote control.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



- NARA 2030**
 Iron frame available. See also page 139
- 170200 **NARA 2030** , Internal 9V battery
 - 170100 **NARA 2030 E**, 9V Transformer





FREE SERIES

Exposed electronic flush valve for urinal operated by IR sensor


Flushing duration and other settings are adjustable by remote control.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.




FREE


- 113100 **FREE** , Internal 9V battery, Standard
- 113200 **FREE E**, 9V Transformer, Standard
- 800504 **FREE SP** , Internal 9V battery, Includes a 200 mm bended pipe and spray. Option for a 300 mm pipe.



FREE



FREE E



FREE SP

JUPITER 3002 SERIES

Exposed electronic flush valve for urinal Operated by IR sensor
Includes a manual override flush activator button, integral flow regulator, in line filter, high pressure vacuum breaker, and adjustable tail piece. Flushing duration and other settings are adjustable by remote control.


Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



PROX SOLUTIONS


Electronic flush valve kit for urinal
Flushing duration and other settings are adjustable by remote control. Available with detachable body.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.




JUPITER M 0.5 GPF
Side inlet
Manual override flush activator button
Specially designed for the needs of the North American market

- 140112 **JUPITER M 0.5 GPF** , Internal 9V battery
- 140516 **JUPITER ME 0.5 GPF** , 9V Transformer




JUPITER 3002 M
Rear inlet
Manual override flush activator button

- 140215 **JUPITER 3002 M** , Internal 9V battery
- 140315 **JUPITER 3002 EM** , 9V Transformer



PROX KIT FOR URINAL
Suitable for duct concealed installations (plaster walls)

- 620700 **PROX KIT FOR URINAL**, 9V Battery / 9V Transformer



PROX FRONT FIXATION KIT FOR URINALS
Suitable for concrete walls installation

- 620750 **PROX FRONT FIXATION KIT FOR URINALS**, 9V Battery / 9V Transformer




SHOWER PANELS AND SHOWER CONTROLS

	SHOWER HEADS	119		TOUCH SH 1000T	126
	SHOWER PANELS	120-123		THERMIX SH 1000T	127
	NEPTUNE 1042T	124		PROX, WAVE & TOUCH	128
	PERFECT TIME 1042T	124		FOOT WASHFREE	129
	NEPTUNE MEDICAL	125		EXTREME PETITE CS/ EXTREME FW	130


SHOWER HEADS

- Solid brass shower heads
- Advantages:
- Drastically reduces water consumption
 - Built in filter
 - Silicon nozzels in spray disk for easy cleaning

WATER SAVING OPTIONS		
9 LPM	2.38 GPM	FLOW RESTRICTOR
7 LPM	1.85 GPM	FLOW RESTRICTOR
6 LPM	1.59 GPM	FLOW RESTRICTOR
5 LPM	1.06 GPM	FLOW RESTRICTOR



- 600400 **SH 9000**, Rear inlet



- 600100 **SH 3000**, Top inlet




- 07240046 **SLEEVE KIT FOR SH 9000**, Accessory
For high security installations




NEPTUNE SHOWER PANELS

- Electronic Shower Panel**
- Operated by IR sensor. Series includes options for wave or prox operation, cold or premixed water as well as thermostatic controlled hot and cold water.
- Default Wave Operation:**
- Allows activation of the shower once the users place their hands at a close proximity to the sensor. Water will shut off if the users place their hands at a close proximity to the sensor again or once a factory set flow time of 120 seconds will pass. Flow time is adjustable by remote control.
- Optional Prox Operation:**
- Allows automatic activation when the users are within the sensor range, and stops when the users go out of the sensor range.

WATER SAVING OPTIONS		
9 LPM	2.38 GPM	FLOW RESTRICTOR
7 LPM	1.85 GPM	FLOW RESTRICTOR
6 LPM	1.59 GPM	FLOW RESTRICTOR
5 LPM	1.06 GPM	FLOW RESTRICTOR



- NEPTUNE SHOWER PANEL**
- Exposed installation
- 601410 **NEPTUNE SHOWER PANEL B**, 6 x 1.5 AA Batteries
 - 603410 **NEPTUNE SHOWER PANEL E**, 9V Transformer



- NEPTUNE SHOWER PANEL 1000 T**
- Exposed installation. Thermostop operation included, to stop waterflow at 38°C
- 602410 **NEPTUNE SHOWER PANEL 1000 TB**, 6 x 1.5 AA Batteries
 - 604410 **NEPTUNE SHOWER PANEL 1000 TE**, 9V Transformer


PERFECT TIME

SHOWER PANELS

Self closing shower panel operated by touch with Piezo button in the shower panel

Series includes options for cold or premixed water, long version, thermostatic controlled hot and cold water, and versions with an additional hand shower.


WATER SAVING OPTIONS		
9 LPM	2.38 GPM	FLOW RESTRICTOR
7 LPM	1.85 GPM	FLOW RESTRICTOR
6 LPM	1.59 GPM	FLOW RESTRICTOR
5 LPM	1.06 GPM	FLOW RESTRICTOR



PERFECT TIME SHOWER PANEL

Exposed installation

- 601400 **PERFECT TIME SHOWER PANEL B**, 6 x 1.5 AA Batteries
- 603400 **PERFECT TIME SHOWER PANEL E**, 9V Transformer




PERFECT TIME SHOWER PANEL1000 TB

Exposed installation

Thermostatic mixing handle to adjust water temperature

- 602400 **PERFECT TIME SHOWER PANEL 1000 TB**, 6 x 1.5 AA Batteries
- 604400 **PERFECT TIME SHOWER PANEL 1000 TE**, 9V Transformer



PERFECT TIME SHOWER PANEL1000 T WITH HAND SHOWER

Exposed installation

Thermostatic mixing handle to adjust water temperature

Hand shower diverter

- 602401 **PERFECT TIME SHOWER PANEL 1000 TB W/ HAND SHOWER**, 6 x 1.5 AA Batteries
- 604401 **PERFECT TIME SHOWER PANEL 1000 TE W/ HAND SHOWER**, 9V Transformer

LONG PANEL

PERFECT TIME SHOWER PANEL L

Exposed installation

Long panel 140 cm

- 601402 **PERFECT TIME SHOWER PANEL LB**, 6 x 1.5 AA Batteries





PERFECT TIME M

SHOWER PANELS

Self-closing shower panel. Manually activated
Incorporates an aluminum panel and vandal resistant shower head with easily cleanable silicone nozzles. The water flow will automatically shut off after a factory set flow time.

WATER SAVING OPTIONS		
9 LPM	2.38 GPM	FLOW RESTRICTOR
7 LPM	1.85 GPM	FLOW RESTRICTOR
6 LPM	1.59 GPM	FLOW RESTRICTOR
5 LPM	1.06 GPM	FLOW RESTRICTOR




PERFECT TIME SHOWER PANEL TM
Exposed installation
Thermostatic mixing handle to adjust water temperature
Flow time is adjustable onsite to a maximum of 2 min
For hot and cold water
• 607100 **PERFECT TIME SHOWER PANEL TM**

PERFECT TIME SHOWER PANEL M
Exposed installation
Flow time is adjustable onsite to a maximum of 2 min
For cold or premixed water
• 607200 **PERFECT TIME SHOWER PANEL M**

NEPTUNE 1042 T

ELECTRONIC SHOWER CONTROL

Operated by IR sensor
Series includes options for wave or prox operation. Features an integrated thermostatic mixer for anti scalding operation and temperature control.




NEPTUNE 1042 T
Exposed installation
• 612280 **NEPTUNE 1042 T**, Internal 9V battery
• 612281 **NEPTUNE 1042 TE**, 9V Transformer
Concealed installation in concrete or brick walls.
Thermostatic mixing handle to adjust water temperature
Allows activation of the shower once the users place their hands at a close proximity to the sensor.
Water will shut off if the users place their hands at a close proximity to the sensor again or once a factory set flow time of 120 seconds will pass.
The flow time is adjustable on site by remote control.
Optional Prox Operation:
Allows automatic activation when the users comes within the sensor range, and stops when the users leave the sensor range.

PERFECT TIME 1042 T

ELECTRONICALLY OPERATED SELF CLOSING SHOWER CONTROL ACTIVATED BY TOUCH

Operated by a Piezo button integrated in the shower control
Features an integrated thermostatic mixer for an anti scalding operation and temperature control.




PERFECT TIME 1042 T
Concealed installation in concrete or brick walls
• 612253 **PERFECT TIME 1042 T**, Internal 9V battery
• 612254 **PERFECT TIME 1042 TE**, 9V Transformer
Thermostatic mixing handle to adjust water temperature
When a user touches the designated area in the middle of the Piezo element a flow cycle of 120 seconds is activated.
If the user wants to stop the water flow, he can touch the piezo area again before the default time has passed, thus, saving more water.

NEPTUNE MEDICAL


ELECTRONIC SHOWER CONTROL

Operated by IR sensor
 Features an integrated thermostatic mixer for anti scalding operation and temperature control.
 Allows activation of the shower once the users place their hands at a close proximity to the sensor. Water will shut off if the users place their hands at a close proximity to the sensor again or once a factory set flow time of 120 seconds will pass. Flow time is adjustable by remote control.
Optional Prox Operation:
 Allows automatic activation when the users comes within the sensor range, and stops when the users leave the sensor range.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



NEPTUNE MEDICAL 1000 T
 Exposed installation
 • 610250 **NEPTUNE MEDICAL 1000 T**, Internal 9V battery




NEPTUNE MEDICAL 1000 T BOTTOM OUTLET
 Exposed installation
 Bottom outlet
 • 610255 **NEPTUNE MEDICAL 1000 T BOTTOM OUTLET**, Internal 9V battery

TOUCH SH 1000 T


ELECTRONICALLY OPERATED SELF CLOSING SHOWER CONTROL ACTIVATED BY TOUCH

Operated by a Piezo element integrated in the shower control
 Features an integrated thermostatic mixer for anti scalding operation and temperature control.

Hygiene Flush: To maximize hygiene, this product is equipped with a 24 hour duty flush. The flush takes place after 24 hours of non-use. Prevents the trap seal from drying out, possible freezing of pipes and potential bacteria in standing water. This function can be disabled using the remote control.



TOUCH SH 1000 T
 Exposed installation
 • 610710 **TOUCH SH 1000 T**, Internal 9V battery



TOUCH SH 1000 T BOTTOM OUTLET
 Exposed installation
 Bottom outlet
 • 610700 **TOUCH SH 1000 T BOTTOM OUTLET**, Internal 9V battery

THERMIX SH 1000T

SHOWER CONTROL

Wall mounted thermostatic shower control with bottom outlet

Reassures safety and allows for maximum comfort in commercial or residential washrooms. The Thermix, Stern’s thermostatic manual line is part of Stern’s thermostatic collection.


- 100% chrome plated brass body
- All the parts are accesible from the front

THERMIX SH 1000 T

Exposed installation

Manual operation

- 610400 THERMIX SH 1000 T



PROX, WAVE & TOUCH SOLUTIONS

TOUCH FREE & TOUCH OPERATED SHOWER KITS

Operated by an IR sensor or a Piezo button

Can be integrated with a shower panel, shower control or as an individual unit.
For cold or premixed water.


PICTURE	PRODUCT NAME	MODEL FEATURES	POWER SUPPLY	CODE NUMBER	DRAWING
	PROX KIT FOR SHOWER	Concealed installation in dry or plaster wall. Option for front fixation installation in concrete, brick walls. Available with detachable body. Touch free Prox Operation Allows automatic activation when the users bring their hands within the sensor range, and stops when the users remove their hands.	9V battery / 9V transformer	620000	
	WAVE KIT FOR SHOWER	Concealed installation in dry or plaster wall. Option for front fixation installation in concrete, brick walls. Available with detachable body. Touch free Wave Operation Allows activation of the shower once the users place their hands at a close proximity to the sensor. Water will shut off if the users place their hands at a close proximity to the sensor again or once a factory set flow time of 120 seconds will pass. Flow time is adjustable by remote control.	9V battery / 9V transformer	620810	
	PROGRAMMABLE PIEZO KIT FOR SHOWER	Concealed installation in dry or plaster wall. Option for front fixation installation in concrete, brick walls. Touch Operation Allows activation of the shower / unit once the users touch the designated area in the Piezo button. Water will shut off if the users touch the designated area again or once a factory set flow time of 120 seconds will pass.	9V battery / 9V transformer	07225019	
	APS THREADED ROD KIT SHOWER	Threaded rod solution for piezo kits installations in thick walls. Kit includes Piezo switch, threaded rod with rosette and solenoid valve. Touch Operation Allows activation of the shower / unit once the users touch the designated area in the Piezo button. Water will shut off if the users touch the designated area again or once a factory set flow time of 120 seconds will pass.	9V battery / 9V transformer	07226054	
	PPS HIGH SECURITY KIT FOR SHOWER	Specially designed for high security environments. The kit includes a shower head and piezo switch that are incorporated in a brass sleeve. For concealed installation in concrete, brick walls.	Not included	07226033	
	PROGRAMMABLE PIEZO KIT FOR BEACH SHOWER COLUMNS	Self-closing piezo kit for showers. Activated by touching the designated area. Kit includes a programmable piezo switch, solenoid valve with housing. Filter and valve are located in the IP67 waterproof dual power input box. The shower will automatically shut off after a factory set flow time of 30 seconds would pass. Flow time adjustable on site if required. Dual power input box can be used to operate the product by battery or transformer. When used with a transformer it has an integrated automatic battery backup.	9V battery / 9V transformer	07226050	
	PERFECT TIME SH CONTROL ASSEMBLY WPC	Electronically operated self closing shower panel operated by touch. Operated by a Piezo button in the shower panel. Includes the control panel only. Electronically operated self closing aluminum shower panel operated by a Piezo touch button. Includes the control panel only. No moving parts, ideal for heavy duty areas. Non hold open feature. Aluminum panel with Epoxy coating for high corrosion resistance. Provides a retrofit solution for old shower systems.	Not included	07040312	

FOOT WASHFREE


ELECTRONICALLY OPERATED SELF CLOSING FOOT WASHER ACTIVATED BY TOUCH

Operated by a Piezo element integrated in the foot washer cap.
For cold or premixed water.
Ideal for swimming pools, beaches and ritual foot washing.
Heavy duty chrome plated brass construction.
Silicone nozzles for easy cleaning.

WATER SAVING OPTIONS		
9 LPM	2.38 GPM	FLOW RESTRICTOR
7 LPM	1.85 GPM	FLOW RESTRICTOR
6 LPM	1.59 GPM	FLOW RESTRICTOR



FOOT WASHFREE
Exposed installation
• 113730 **FOOT WASHFREE**, Internal 9V battery



FOOT WASHFREE 3000
Exposed installation
Directional shower head
• 113720 **FOOT WASHFREE 3000**, Internal 9V battery




NEW!


EXTREME PETITE CS/FW

TOUCH-FREE WALL-MOUNTED ELECTRONIC FOOT WASHER FAUCETS

Activated by a concealed sensor integrated into the spout.
For cold or premixed water.
For concealed installations.
Suitable for worship centers as well as for swimming pools and beaches, where maintaining high standards of hygiene is required.



EXTREME PETITE CS
Exposed installation
• 237818 **EXTREME PETITE CS E**, 9V Transformer
• 237840 **EXTREME PETITE CS DPE**, 9V Transformer
• 237819 **EXTREME PETITE CS DPE AISI316**, 9V Transformer



EXTREME FW
Exposed installation
• 237709 **EXTREME FW**, 9V Transformer





PROGRAMMING SOLUTIONS & COMPONENTS



CONNECTED WASHROOMS

133



PLUG IN TRANSFORMERS FOR FAUCETS, URINALS, TOILETS, AND SHOWERS

138



REMOTE CONTROLS

134



IP68 ENCAPSULATED TRANSFORMERS FOR FAUCETS, URINALS, TOILETS, AND SHOWERS FOR WET AREAS

139



MIXING VALVES

135



IP68 ENCAPSULATED SWITCHING TRANSFORMERS FOR CISTERNS

139



COVER PLATE

136




TRANSFORMERS FOR SOAP DISPENSERS

140



SOLENOID KEY

136



POWER SPLITTERS

140



UNIVERSAL PROPRIETARY SOAP ADAPTORS

137



CABLE EXTENSIONS

141



JUNCTION BOXES

138





BATTERY BOXES

141

CONNECTED WASHROOMS


INTELLIGENT WASHROOM MONITORING & MANAGEMENT SYSTEM

- Remote management, control, and monitoring of all STERN products on site
- Optimal resources management
- Real time usage info, issues alerts, soap refill alerts
- Enhancement of hygiene, watersaving and safety.
- Building Management efficiency enhancement along quick and accurate daily attendance and reduction of ongoing cleaning, labor and maintenance costs.



To enjoy the full functionality of the Stern Hi-Tech app as a controller for your smart sanitary products, please follow these steps:

1. Confirm compatibility with your Stern representative to ensure your product supports the Stern Bluetooth app.
2. Download the app from the Google Play Store
3. Connect and enjoy a seamless smart control experience.



REMOTE CONTROLS

REMOTE CONTROL

Allows easy maintenance of extensive installations requiring custom settings. The remote control allows adjustment of sensor features for all Stern electronic products, while some functions require a compatible product model:

- Sensor range
- Entrance to the self adjustment mode
- Security time
- Short flow time
- Flow time
- Delay in
- Delay out
- 24 hour hygiene flush
- Lock out time
- Temporary off
- Reset

Code Number: 07100005



SOAP & WATER REMOTE CONTROL

In addition to the possibility to change settings at liquid or foam soap dispensers, this remote control allows to change settings at Stern matching touch free faucets. The following functions and settings can be changed:

- Sensor range
- Soap quantity in foam Soap Dispensers
- Entrance to the self-adjusting mode in wall mounted faucets
- Soap tank refill
- Temporary shut off
- Air quantity in foam soap dispensers
- Reset to factory settings
- Liquid Soap Quantity 1 - 4

Code Number: 07100014

LIQUID SOAP DISPENSERS REMOTE CONTROL



- Adjustable settings:**
- Soap dosage
 - Temporary shutoff function
 - Soap tank refill
 - Reset to factory settings

Code Number: 07100008

FOAM SOAP DISPENSERS REMOTE CONTROL




- Adjustable settings:**
- Soap dosage
 - Air quantity
 - Temporary shutoff function
 - Soap tank refill
 - Reset to factory settings

Code Number: 07100009

UNDERBASIN TMV


THERMOSTATIC MIXING VALVE

- Advantages:**
- Easy installation, connects directly to angle valves under the basin
 - Thermostatic control for optimum temperature
 - Can connect up to 4 faucets simultaneously
 - Includes hot water stop function to prevent scalding
 - Built-in filters to prevent dirt entering the system
 - Back check valves prevent hot water entering cold water inlet




UNDERBASIN TMV

- G 3/8" inlet
- 07200069 **UNDERBASIN TMV**, (without connection kit) 1 unit
 - 07200069-US **UNDERBASIN TMV**, (with connection for US) 1 unit
 - 07200075 **UNDERBASIN TMV**, (without connection kit) 12 units
 - 07200073 **UNDERBASIN TMV**, (with connection for US) 12 units
- 07291113 **UNDERBASIN TMV CONNECTION KIT**,
Includes 1 x flexible hose 3/8", 1 x 90° brass arch, 1 x T-piece 3/8"



INTEGRATED THERMOSTATIC MIXING VALVE

- G - 1/2" inlet
- Includes built in filters and check valves.
 - Easy installation
 - Thermostatic control for optimum temperature
 - For 1 to 6 sanitary points of use(depending on flow rate) .
- 07010198 **INTEGRATED THERMOSTATIC MIXING VALVE**
- 07201001 **INTEGRATED THERMOSTATIC MIXING VALVE 6-PACK**





STERN MIXING VALVE


- Mechanical Mixing Valve Includes built in filters and check valves.
- Easy installation
 - An easy-to-use adjustment allowing pre-mix of hot and cold water.
 - Enables the technical staff to manually set the water temperature .. at any given time.
- 200060 **STERN MIXING VALVE 3/8"**,G - 3/8" inlet
- 200065 **STERN MIXING VALVE 3/8" WITH NUT**, G - 3/8" inlet
- 200070 **STERN MIXING VALVE 1/2"**, G - 1/2" inlet

COVER PLATE KIT


- Offers a solution for deck mounted faucets to cover unused mounting holes. 28 mm / 4" deck plate kit.**
- One hole cover plate, for single hole mount faucets.
 - Covers 28 mm diameter / 4" mounting holes
 - Complete kit with gasket and screw




07270290
COVER PLATE 4"
ANTI-ROTATION KIT
FOR CLASSIC CS



07270288
COVER PLATE 4"
ANTI-ROTATION
KIT
FOR CSABA



07275005
COVER PLATE 4"
ANTI-ROTATION KIT
FOR EASY 1000




07270291
COVER PLATE 4"
ANTI-ROTATION KIT
FOR TRENDY/
EXTREME

SOLENOID KEY



- Specially designed customed key for easy maintenance of the Stern solenoid valves.
- Code Number: 07590009



PROPRIETARY SOAP ADAPTOR KITS

Now you can connect any container of soap that is compatible with Stern's soap dispenser using our Universal Proprietary Soap Adaptors. Adaptors come in two sizes: 45 - 59 mm, and 30 - 38 mm to easily connect any soap container.



DRAWING	PRODUCT NAME	DESCRIPTION	PART NUMBER
	2L UNDERBASIN TANK CONVERSION KIT	Includes: 2L soap container, breathe pipe, rubber seals and mounting support. To be used with Stern soap dispenser models.	07247011
	SMALL PROPRIETARY SOAP ADAPTOR	Includes: small elastic cover adaptor for use with proprietary individual soap containers. Soap container opening outer min/max diameters including thread: 30mm-38mm	07270294
	SMALL PROPRIETARY SOAP ADAPTOR FOR MF	Includes: small elastic cover adaptor for use with proprietary soap containers. For multifeed up to 3 products. Soap container opening outer min/max diameters including thread: 30mm-38mm	07270295
	BIG PROPRIETARY SOAP ADAPTOR	Includes: big elastic cover adaptor for use with proprietary individual soap containers. Soap container opening outer min/max diameters including thread: 45mm-59mm	07270296
	BIG PROPRIETARY SOAP ADAPTOR FOR MF	Includes: big elastic cover adaptor for use with proprietary soap containers. For multifeed up to 3 products. Soap container opening outer min/max diameters including thread: 45mm-59mm	07270297

JUNCTION BOXES

DRAWING	PRODUCT NAME	MODEL FEATURES	INPUT VOLTAGE	OUTPUT VOLTAGE	FREQUENCY	OUTPUT CURRENT	CODE NUMBER
 	JUNCTION BOX WITH TRANSFORMER FOR FAUCETS, URINALS, TOILETS AND SHOWERS	Connection point of up to 10 products together. Includes a 12VDC 2 Amp power supply transformer	115-230V	12V	60 HZ	2.1 A	06530013
	JUNCTION BOX WITH TRANSFORMER FOR SOAP DISPENSERS	Connection point of up to 10 Soap Dispensers or 10 ring illuminated products. Includes a 12VDC 4.2 Amp power supply transformer.	115-230V	12V	60 HZ	4.2 A	06530062

CABLES FOR JUNCTION BOX			
DRAWING	PRODUCT NAME	MODEL FEATURES	CODE NUMBER
	OUTPUT CABLE FOR JUNCTION BOX	3 meters male connector	06000084
	OUTPUT CABLE FOR JUNCTION BOX	3 meters female connector	06000086

PLUG IN TRANSFORMERS FOR FAUCETS, URINALS, TOILETS AND SHOWERS







Transformers with 5 meter cable male/female waterproof connector (CE, RoHS, UL).

TECHNICAL CHARACTERISTICS	
INPUT VOLTAGE	100 - 240V
OUTPUT VOLTAGE	9V
FREQUENCY	50 - 60 HZ
OUTPUT CURRENT	500 MA

PICTURE	PRODUCT NAME	CONNECTOR	CODE NUMBER	12-PACK CODE
	SWITCHING TRANSFORMER EU	MALE	06522091	06540002
		FEMALE	06522094	06540003
	SWITCHING TRANSFORMER UK	MALE	06522088	06540004
		FEMALE	06522093	06540005
	SWITCHING TRANSFORMER US	MALE	06522115	06540006
		FEMALE	06522116	06540007
	SWITCHING TRANSFORMER AU	MALE	06522089	06540008
		FEMALE	06522095	06540009

IP68 SWITCHING TRANSFORMERS FOR FAUCETS, URINALS, TOILETS, AND SHOWERS






IP68 Switching transformer for wet areas with 5m cable and male/female waterproof connector (CE,RoHS,CB).

PICTURE	PRODUCT NAME	CONNECTOR	INPUT VOLTAGE	OUTPUT VOLTAGE	FREQUENCY	OUTPUT CURRENT	CODE NUMBER
	IP68 SWITCHING NO PLUG	MALE 	110-240V	9V	50/60 Hz	600 mA	06522171
		FEMALE 					06522172
	IP68 SWITCHING EU	MALE 	110-240V	9V	50/60 Hz	600 mA	06522168
		FEMALE 					06522169
	IP68 SWITCHING UK	MALE 	110-240V	9V	50/60 Hz	600 mA	06522165
		FEMALE 					06522166
	IP68 SWITCHING US	MALE 	110-240V	9V	50/60 Hz	300 mA	06522099
		FEMALE 					06522100
	IP68 SWITCHING AU	MALE 	110-240V	9V	50/60 Hz	300 mA	06522103
		FEMALE 					06522104

IP68 ENCAPSULATED SWITCHING TRANSFORMER FOR CISTERNS

IP68 Encapsulated switching transformer with 5 meter cable and male/ female waterproof connector (CE, RoHS,UL). Suitable for multiple products installation with electrical connection when combined with the appropriate power splitter. See page 151.











PRODUCT NAME	CONNECTOR	INPUT VOLTAGE	OUTPUT VOLTAGE	FREQUENCY	OUTPUT CURRENT	CODE NUMBER
IP68 ENCAPSULATED SWITCHING TRANSFORMER EU PLUG FOR CISTERNS	MALE 	110-240V	12V	50/60 HZ	2.5 A	06522077
	FEMALE 					06522078
IP68 ENCAPSULATED SWITCHING TRANSFORMER UK PLUG FOR CISTERNS	MALE 	110-240V	12V	50/60 HZ	2.5 A	06522071
	FEMALE 					06522072
IP68 ENCAPSULATED SWITCHING TRANSFORMER US PLUG FOR CISTERNS	MALE 	110-240V	12V	50/60 HZ	2.5 A	06522125
	FEMALE 					06522126

TRANSFORMERS FOR SOAP DISPENSERS

12V switching adaptor with 5 meter cable and male waterproof connector.

PICTURE	PRODUCT NAME	INPUT VOLTAGE	OUTPUT VOLTAGE	FREQUENCY	OUTPUT CURRENT	CODE NUMBER
	12V TRANSFORMER - UNIVERSAL INCLUDES PLUGS F OR EU, US AND UK	110-240V	12V	50/60 Hz	500 mA	06522082
	12V TRANSFORMER - EU	110-240V	12V	50/60 Hz	500 mA	06522081-U
	12V TRANSFORMER - USA	110-240V	12V	50/60 Hz	500 mA	06522117
	12V TRANSFORMER - AU	110-240V	12V	50/60 Hz	500 mA	06522085-U
	12V TRANSFORMER - UK	110-240V	12V	50/60 Hz	500 mA	06522086-U


POWER SPLITTERS

DRAWING	PRODUCT NAME	MODEL FEATURES	CODE NUMBER
	POWER SPLITTER 2 WAYS F-M2	Cable length to product: 100 mm Cable length to power supply: 100 mm	06001034
	POWER SPLITTER 2 WAYS M-F2	Cable length to product: 100 mm Cable length to power supply: 100 mm	06001038
	POWER SPLITTER 3 WAYS F-M3	Cable length to product: 100 mm Cable length to power supply: 100 mm	06001036
	POWER SPLITTER 2 WAYS M-F3	Cable length to product: 100 mm Cable length to power supply: 100 mm	06001035
	POWER SPLITTER SOAP & WATER 2 WAYS F-M/F	To be used with 12V transformer. For connection of one soap dispenser and one faucet. Cable length to product: 100 mm. Cable length to power supply: 100 mm	06001025
	POWER SPLITTER SOAP 2 WAYS F-M2	To be used with 12V, 2.5 A transformer. For multiple connection of 2 soap dispensers. Cable length to product: 500 mm Cable length to power supply: 100 mm	06001026
	POWER SPLITTER SOAP 3 WAYS F-M3	To be used with 12V, 2.5 A transformer. For multiple connection of 3 soap dispensers. Cable length to product: 1X500 mm, 2X1500 mm. Cable length to power supply: 100 mm	06001027
	POWER SPLITTER SOAP 4 WAYS F-M4	To be used with 12V, 2.5 A transformer. For multiple connection of 4 soap dispensers. Cable length to product: 2X500 mm, 2X1500 mm. Cable length to power supply: 100 mm	06001028

CABLE EXTENSION

DRAWING	PRODUCT NAME	CODE NUMBER
	CABLE EXTENSION 100 MM MALE/FEMALE	06000064
	CABLE EXTENSION 100 MM MALE/MALE	06009018
	CABLE EXTENSION 100 MM FEMALE/FEMALE	06009022
	CABLE EXTENSION 100 MM MALE/FEMALE	06000004
	CABLE EXTENSION 100 MM FEMALE/OPEN	06000003
	CABLE EXTENSION 100 MM MALE/BATTERY	06000029
	CABLE EXTENSION 100 MM FEMALE/BATTERY	06000050

BATTERY BOXES

PICTURE	PRODUCT NAME	RERQUIRED BATTERIES	CONNECTOR	CODE NUMBER	12- PACK CODE	15-PACK CODE
	IP67 BLACK BATTERY BOX	6x1.5V AA batteries	Male waterproof connector	06530092	N/A	06533002
		6x1.5V AA batteries (Not supplied)		06530096	N/A	06533000
		6x1.5V AA batteries	Female waterproof connector	06530093	N/A	06533003
		6x1.5V AA batteries (Not supplied)		06530091	N/A	06533001
	IP67 9V BLACK BATTERY BOX	9V Battery (Alkaline or Lithium - Not supplied)	Male waterproof connector	06530080	N/A	N/A
			Female waterproof connector	06530089	N/A	N/A
	BATTERY BOX FOR SOAP DISPENSERS	6xD batteries (Not supplied)	Male waterproof connector	06530041	N/A	N/A

